

ISLEVER

117-303

LPI Level 3 Exam 303

DEMO

<https://www.islever.com/117-303.html>

<https://www.islever.com/lpi.html>

For the most up-to-date exam questions and materials, we recommend visiting our website, where you can access the latest content and resources.

QUESTION NO: 1

An administrator has just configured an OpenVPN client. Upon starting the service, the following message is displayed:

TLS Error: TLS key negotiation failed to occur within 60 seconds

Which of the following statements is true?

- A. The client was unable to establish a network connection with the server.
- B. The client was able to establish a network connection with the server, however TLS key negotiation failed, resulting in a fallback to SSL.
- C. The client was able to establish a network connection with the server, however TLS and SSL security are not enabled.
- D. The client was able to establish a network connection with the server, however TLS key negotiation took longer than 60 seconds, indicating that there may be a problem with network performance.

Answer: A

QUESTION NO: 2

SELinux has just been installed on a Linux system and the administrator wants to use SELinux in permissive mode in order to audit the various services on the system. What command will switch SELinux into permissive mode?

- A. `setenforce 0`
- B. `/etc/init.d/selinux stop`
- C. `selinux passive`
- D. `/etc/init.d/selinux startpassive`

Answer: A

QUESTION NO: 3

Which of the following export options, when specified in `/etc/exports`, will tell the server to use the NFSv4 Pseudofilesystem?

- A. `fsid=2`
- B. `fsid=0`
- C. `fsid=3`
- D. `fsid=1`

Answer: B

QUESTION NO: 4

Which of the following are common techniques for securing a sendmail server? (Select THREE correct answers)

- A. Maintain user accounts in an LDAP directory.
- B. Enable TLS.
- C. Disable VRFY.
- D. Runsendmail in a chroot'd environment.
- E. Disable USRLKUP.

Answer: B,C,D

QUESTION NO: 5

What does ntop use for data collection?

- A. Network packets
- B. Log files
- C. Frame relay
- D. SNMP

Answer: A

QUESTION NO: 6 CORRECT TEXT

An administrator has successfully configured a cryptographic volume for dmccrypt, and has added the following line to /etc/fstab:

```
/dev/mapper/cryptvol /media/crypt auto defaults 0 0
```

Upon booting the system, the error message "mount: special device /dev/mapper/cryptvol does not exist" is displayed. What configuration file has the administrator forgotten to edit? (Provide the full path and filename)

Answer: /etc/crypttab

QUESTION NO: 7 CORRECT TEXT

What command will remove the dmccrypt mapping named cryptvol? (Provide the command with any options and parameters)

Answer: /sbin/cryptsetup remove crypt-vol cryptsetup remove crypt-vol

QUESTION NO: 8 CORRECT TEXT

Which LUKS action, when supplied to the cryptsetup command, will initialize a LUKS partition and set the initial key? (Provide only the action name)

Answer: luksFormat

QUESTION NO: 9

An administrator has created a mapping with the following command:

cryptsetup luksOpen /dev/sda1 cryptvol and has set three different keys. Which command below will delete the first key?

- A. cryptsetup luksDelKey /dev/sda1 0
- B. cryptsetup luksDelKey /dev/sda1 1
- C. cryptsetup luksDelKey /dev/mapper/cryptvol 1
- D. cryptsetup luksDelKey /dev/mapper/cryptvol 0

Answer: A

QUESTION NO: 10 CORRECT TEXT

What command will list basic information about all targets available to cryptmount? (Provide the command with any options or parameters)

Answer: cryptmount

QUESTION NO: 11

Which of the following are valid dmccrypt modes? (Choose THREE correct answers)

- A. XTS
- B. ESSIV
- C. GMR
- D. KWG
- E. LRW