# 156-816

Check Point Certified Managed Security Expert
Plus VSX NGX

DEMO

**QUESTION NO: 1**

VSX clusters are defined at two levels:

A. VSX cluster and physical device
B. VSX cluster and virtual device
C. VSX Gateway and physical device
D. VSX cluster and VSX Gateway
E. VSX Gateway and Virtual device

**Answer: E**

**QUESTION NO: 2**

What is the term used to describe a port or interface that shares traffic from more than one VLAN?

A. VLAN riding
B. VLAN trunking
C. Frame-Strata enabled
D. Comprehensive Layer-2 label support
E. Comprehensive VLAN Tag support

**Answer: B**

**QUESTION NO: 3**

TRUE or FALSE. A Virtual System in Bridge Mode can enforce anti-spoofing definitions.

A. False, anti-spoofing can't be configured for Virtual systems in Bridge Mode
B. True, as long as the Virtual System has more than two interfaces defined
C. True, anti-spoofing must be manually defined in bridge mode
D. True, as long as Network Address Translation is performed
E. True, anti-spoofing measures are defined automatically is Bridge mode

**Answer: C**

**QUESTION NO: 4**

The _____ interface is configured in a VLAN environment, to allow multiple Virtual systems to share a single physical interface on a VSX Gateway.

A. Synchronization

B. Warp

C. Symbolic

D. Virtual

E. Physical

**Answer: D**


## QUESTION NO: 5

At installation, the _____ is bound to all configured physical interfaces of a VSX Gateway, UNLESS the interfaces are specifically assigned to another component.

A. VSX Management Server

B. Synchronization Network

C. Internal Virtual Router

D. External Virtual Router

E. Management Virtual System

**Answer: E**


## QUESTION NO: 6

The provisioning and network configuration channel does NOT:

A. Create Virtual Systems and Virtual Routers on a Gateway

B. Install Administrator defined Security Policies

C. Install a default Security Policy blocking all traffic

D. Create a SCI Certificate for new objects and transfer the Certificate to an object on the VSX Gateway

E. Configure interface and routing information on the Gateway

**Answer: B**


## QUESTION NO: 7

Which of the following is a type of VLAN membership?

A. Port-based

B. Time-based

C. Session-based

D. Protocol-based

E. Application-based

**Answer: D**

## QUESTION NO: 8

Which of the following is NOT a type of physical interface seen in a VSX Gateway?

A. Dedicated management
B. Synchronization
C. External
D. Internal
E. Warp

**Answer: E**

## QUESTION NO: 9

A Virtual System in Bridge Mode is a Virtual System that implements:

A. Dynamic IP Routing
B. Network Address Translation
C. IP Routing
D. Native Layer-2 Communications
E. VLAN Tagging

**Answer: D**

## QUESTION NO: 10

Which of the following virtual devices will NOT fail over, if its interface fails in a VSX High Availability configuration?

A. Management Virtual System Interfaces
B. External Virtual Router
C. Virtual Switch
D. Virtual System with VLAN Interfaces
E. Virtual System with dedicated interfaces

**Answer: C**