

I S L E V E R

1V0-642

VCA6 - Network Virtualization 6.2 Exam

DEMO

<https://www.islever.com/1v0-642.html>

<https://www.islever.com/vmware.html>

For the most up-to-date exam questions and materials, we recommend visiting our website, where you can access the latest content and resources.

QUESTION 1

An organization has not yet implemented network virtualization in their IT infrastructure.

What are the two common management challenges organizations meet in their day-to-day administration?

(Choose two.)

- A. Be susceptible to malware and virus vulnerabilities in the network.
- B. Update physical network manually each time a new application is deployed.
- C. Spend more time in provisioning and decommissioning lab environments.
- D. Manage frequently occurring network requests manually.

Answer: BC

QUESTION 2

How do virtual networks support physical infrastructure Quality of Service (QoS)?

- A. By receiving the help of the NSX gateway.
- B. By marking the packets in the encapsulated header.
- C. By employing East-West traffic.
- D. By restricting the access of VLANs to specific pods.

Answer: B

QUESTION 3

Which characteristic of VMware NSX enables secure intra-data center network traffic?

- A. Micro-segmentation
- B. Cloud pod architecture
- C. Elasticity
- D. Multi-tenant manageability

Answer: B

QUESTION 4

An administrator is working in an IT infrastructure where traditional routing methods are followed for routing network traffic. What are the three challenges for an administrator in this infrastructure? (Choose three.)

- A. The use of East-West traffic is not secure within a data center.
- B. North-South routing methods limit data center scalability.
- C. The complexity of routing increases in a multi-tenant environment.
- D. A suboptimal traffic route is used to reach destination.
- E. Adding new servers to an isolated network became difficult.

Answer: A

QUESTION 5

How can the legacy physical network be simple, stable and reliable when network abstraction is implemented?

- A. By leveraging the existing physical devices without configuration changes.
- B. By automating services for provisioning new services.
- C. By configuring new VLANs.
- D. By integrating third-party devices with the existing infrastructure.

Answer: D

QUESTION 6

What are three common problems for administrators when managing application with network security models that are not virtualized? (Choose three.)

- A. Lack of Interoperability and automation creates error-prone manual work.

- B. Integration of third-party security products with home products is not possible.
- C. Deploying and managing third-party security products become difficult.
- D. Load balancing by vMotion is not possible.
- E. There is limited visibility into a workload's security posture and policies.

Answer: ACE

QUESTION 7

What are two functions of a DLR control VM (Choose two.)

- A. Communicates with the NSX manager and sends routing updates to the NSX controller cluster.
- B. Performs Address Resolution Protocol (ARP) entry lookup.
- C. Establishes routing protocol sessions with other routers.
- D. Forms adjacencies with edge routing peers.

Answer: AD

QUESTION 8

What is the total volume of traffic per Distributed Logical Router (DLR) that is supported by the Equal Cost Multipath (ECMP) model?

- A. 20 GB
- B. 50 GB
- C. 80 GB
- D. 40 GB

Answer: C

QUESTION 9