

ISLEVER

1Y0-A24

Citrix XenServer 5.6 Administration

DEMO

<https://www.islever.com/1y0-a24.html>

<https://www.islever.com/citrix.html>

For the most up-to-date exam questions and materials, we recommend visiting our website, where you can access the latest content and resources.

Note: The answer is for reference only, you need to understand all question.

QUESTION 1

A network administrator requested that the XenServer administrator of a resource pool separate virtual machine backup traffic from guest traffic so that virtual machine backup traffic is routed to an external backup server.

Which action must the XenServer administrator take to complete this task?

- A. Create a VLAN for backup traffic
- B. Assign QoS on the backup traffic
- C. Create an internal network for backup traffic
- D. Assign a dedicated interface for the backup traffic

Answer: D

QUESTION 2

To successfully configure Role Based Access Control, an administrator must ensure that Active Directory servers are _____ and _____.

(Choose the two correct upturns to complete the sentence)

- A. SMB enabled
- B. Using LDAP authentication
- C. Using Kerberos authentication
- D. synchronized with XenServer using NTP

Answer: CD

QUESTION 3

Scenario: A resource pool contains three XenServer hosts. An administrator is NOT able to configure the high availability feature.

Which two types of storage are supported by the resource pool? (Choose two)

- A. CIFS
- B. NFS
- C. iSCSI
- D. Fibre Channel

Answer: AB

QUESTION 4

Scenario: Four physical NICs are accessible to XenServer. Two NICs are currently in use. An administrator looks at the performance tab and notices that NIC utilization is approaching maximum bandwidth.

Which can the administrator create to improve performance?

- A. Guest VLAN
- B. Internal network
- C. Bond for management traffic
- D. Bond for guest virtual machine traffic

Answer: D

QUESTION 5

Which scenario would it be appropriate to implement Storage link Gateways in XenServer environment?

- A. Virtual machines will be deployed through Lab Manager
- B. The performance alert and reporting service will be utilized
- C. There must be access to native array configuration features
- D. Multiple network protocols are used in the utilization environment

Answer: C

QUESTION 6

An administrator has to set up a virtual machine to provide DHCP and PXE roles for different provisioning services targets running in different VLANs and subnets.

Which two kinds of networks should the administrator add to this virtual machine? (Choose two)

- A. Bonded network with tagged VLAN option
- B. Internal network with tagged VLAN option
- C. External network with tagged VLAN option
- D. Management network with tagged VLAN option

Answer: AC

QUESTION 7

Scenario: An administrator needs to make a number of CD images available to all of the virtual machines attached to a physical XenServer host the administrator has a single NFS export available on which to store these images. The NFS export has following characteristics.

-ip address 192.168.1.1

-NFS Export /CDs

Which CU command must the administrator execute to create the storage repository?

- A. `xe sr-create host-uuid=<valis_uuid content type=user name label=<*example SR*>location=*\192.168.1.1\cds*`
- B. `xe sr-create host-uuid=<valis_uuid content type=iso name-label=<*example SR*> location=*192.168.1.1:/cds*`
- C. `xe sr-create host-uuid=<valis_uuid content type= iso name-label=<*example SR*> location=*\192.168.1.1:/cds*`
- D. `xe sr-create host-uuid=<valis_uuid content type=user physical-size=7000000 name label=<* example SR*> location=*192.168.1.1:/cds*`

Answer: C

QUESTION 8

Which two steps must an administrator take to license a host in XenServer Enterprise Edition? (Choose 2)

- A. Specify the Citrix License Server name
- B. Add the license file to the Citrix License Server
- C. Apply the UC license file using License Manager
- D. Apply the XSUC license file using License Manager

Answer: AB

QUESTION 9

XenServer administrator wishes to move all iSCSI and NFS storage traffic to dedicated network called "storage network"

Which two steps must the administrator complete to configure the network interface so that only iSCSI and NFS storage traffic use the network interface? (Choose two)

- A. Add the dedicated "storage network" to all virtual machines.
- B. Replace the primary management interface with the new "storage network"
- C. Ensure that the storage repositories are only routable from "storage network" IP subnet