

ISLEVER

# 350-050

CCIE Wireless Beta Written Exam

DEMO

<https://www.islever.com/350-050.html>

<https://www.islever.com/cisco.html>

For the most up-to-date exam questions and materials, we recommend visiting our website, where you can access the latest content and resources.

---

## Topic 1, Volume A

### QUESTION NO: 1

Which two security features are associated with a wireless network employing 802.11i configured as a Robust Security Network? (Choose two.)

- A. WEP
- B. AES-CCMP
- C. 802.11x
- D. IPsec
- E. TKIP
- F. 802.1x

**Answer: B,F**

**Explanation:**

### QUESTION NO: 2

Before conducting a passive RF site survey with a standalone AP, which two of these should be statically configured on the AP? (Choose two.)

- A. passive client
- B. channel assignment
- C. DTPC
- D. Tx power level
- E. channel scan defer priority

**Answer: B,D**

**Explanation:**

### QUESTION NO: 3

After interviewing a customer to understand wireless client requirements, you determine that 802.11b must be enabled to support legacy clients within a mixed-mode environment. Which recommendation will have the greatest impact on mitigating the effects of 802.11b clients on the rest of the network?

- A. Restrict OFDM modulation from being used.
- B. Make 11 Mb/s the lowest mandatory rate.
- C. Enable a separate SSID for 802.11b clients.

---

D. Enable a short preamble.

**Answer: B**

**Explanation:**

**QUESTION NO: 4**

In a Cisco Unified Wireless Network environment, which two of these are required in order for clients to connect with MCS data rates? (Choose two.)

- A. EDCF
- B. client MFP
- C. multiple spatial streams
- D. AES-CCMP
- E. 40-MHz channels

**Answer: A,D**

**Explanation:**

**QUESTION NO: 5**

The 802.11-2007 standard includes which two amendments to the original 802.11 standard? (Choose two.)

- A. 802.11c
- B. 802.11d
- C. 802.11j
- D. 802.11r
- E. 802.11u

**Answer: B,C**

**Explanation:**

**QUESTION NO: 6**

You are designing a wireless network utilizing EAP-TLS. One design requirement is to provide per-user differentiated QoS using only one SSID. What is the best way to achieve this goal?

- 
- A. using WMM override
  - B. using Cisco Airespace VSAs
  - C. using QoS Enhanced BSS
  - D. using AP groups

**Answer: B**

**Explanation:**

#### **QUESTION NO: 7**

What does the letter P in the designation of the AIR-CAP3502P AP indicate?

- A. The AP supports the new IEEE 802.11p (WAVE) wireless standard.
- B. The AP requires professional installation.
- C. The AP can be used in plenum applications.
- D. The AP is compatible with polarization type antennae.

**Answer: B**

**Explanation:**

#### **QUESTION NO: 8**

You are converting your wireless infrastructure from a data-only design to a location services design. Which task do you need to complete?

- A. Disable the DSSS speeds for RFID compatibility.
- B. Use fewer APs to avoid RFID 3D imaging.
- C. Set APs to maximum power for RF fingerprinting.
- D. Locate APs at the edges of your coverage area for trilateration.

**Answer: D**

**Explanation:**

#### **QUESTION NO: 9**

Which statement about heat maps on Cisco WCS is true?

- A. They are predictive and rely only on the accuracy of the information that is provided with the