

ISLEVER

351-018

Security 3.0 Beta

DEMO

<https://www.islever.com/351-018.html>

<https://www.islever.com/cisco.html>

For the most up-to-date exam questions and materials, we recommend visiting our website, where you can access the latest content and resources.

QUESTION NO: 1

In order to reassemble IP fragments into a complete IP datagram, which three IP header fields are referenced by the receiver? (Choose three.)

- A. don't fragment flag
- B. packet is fragmented flag
- C. IP identification field
- D. more fragment flag
- E. number of fragments field
- F. fragment offset field

Answer: C,D,F

Explanation:

QUESTION NO: 2

Which VTP mode allows the Cisco Catalyst switch administrator to make changes to the VLAN configuration that only affect the local switch and are not propagated to other switches in the VTP domain?

- A. transparent
- B. server
- C. client
- D. local
- E. pass-through

Answer: A

Explanation:

QUESTION NO: 3

Which type of VPN is based on the concept of trusted group members using the GDOI key management protocol?

- A. DMVPN
- B. SSLVPN
- C. GETVPN
- D. EzVPN
- E. MPLS VPN
- F. FlexVPN

Answer: C

Explanation:

QUESTION NO: 4

Based on RFC 4890, what is the ICMP type and code that should never be dropped by the firewall to allow PMTUD?

- A. ICMPv6 Type 1 – Code 0 – no route to host
- B. ICMPv6 Type 1 – Code 1 – communication with destination administratively prohibited
- C. ICMPv6 Type 2 – Code 0 – packet too big
- D. ICMPv6 Type 3 – Code 1 – fragment reassembly time exceeded
- E. ICMPv6 Type 128 – Code 0 – echo request
- F. ICMPv6 Type 129 – Code 0 – echo reply

Answer: C

Explanation:

QUESTION NO: 5

A firewall rule that filters on the protocol field of an IP packet is acting on which layer of the OSI reference model?

- A. network layer
- B. application layer
- C. transport layer
- D. session layer

Answer: A

Explanation:

QUESTION NO: 6

Which layer of the OSI model is referenced when utilizing http inspection on the Cisco ASA to filter Instant Messaging or Peer to Peer networks with the Modular Policy Framework?

- A. application layer
- B. presentation layer

-
- C. network layer
 - D. transport layer

Answer: A

Explanation:

QUESTION NO: 7

When a Cisco IOS Router receives a TCP packet with a TTL value less than or equal to 1, what will it do?

- A. Route the packet normally
- B. Drop the packet and reply with an ICMP Type 3, Code 1 (Destination Unreachable, Host Unreachable)
- C. Drop the packet and reply with an ICMP Type 11, Code 0 (Time Exceeded, Hop Count Exceeded)
- D. Drop the packet and reply with an ICMP Type 14, Code 0 (Timestamp Reply)

Answer: C

Explanation:

QUESTION NO: 8

In an 802.11 WLAN, which option is the Layer 2 identifier of a basic service set, and also is typically the MAC address of the radio of the access point?

- A. BSSID
- B. SSID
- C. VBSSID
- D. MBSSID

Answer: A

Explanation:

QUESTION NO: 9

What term describes an access point which is detected by your wireless network, but is not a trusted or managed access point?