ISLEVER

600-211

Implementing Cisco Service Provider Mobility
CDMA Networks (SPCDMA)

DEMO

https://www.islever.com/600-211.html
https://www.islever.com/cisco.html

QUESTION NO: 1

Which interface carries signaling information between PCF and PDSN?

A. A8
B. A9
C. A10
D. A11

Answer: D
Explanation:

QUESTION NO: 2

Which underlying protocol is used for RADIUS messages in CDMA?

A. TCP
B. SCTP
C. UDP
D. ICMP

Answer: C
Explanation:

QUESTION NO: 3

Which protocol is used during PPP negotiation to assign an IP address to the mobile device for a simple IP call?

A. LCP
B. IPCP
C. CHAP
D. EAP

Answer: B
Explanation:

QUESTION NO: 4

Which is an attribute in MIP RRQ?

A. Correlation ID
B. NAS-Identifier
C. Framed-IP-Address
D. Care-of-Address
E. Framed-Interface-ID

Answer: D
Explanation:

QUESTION NO: 5

Which bit in HA Registration Revocation message is used by PDSN/FA to determine Mobile notification?

A. 'A' bit
B. 'I' bit
C. 'M' bit
D. 'R' bit

Answer: B
Explanation:

QUESTION NO: 6

What interface uses PMIPv6?

A. S1
B. S2a
C. S6a
D. STa

Answer: B
Explanation:

QUESTION NO: 7

Where does the UE/Mobile obtain its IPv6 prefix?

A. The address prefix from HSGW VSNCP message
B. The address prefix from HSGW Router Advertisement
C. The address prefix from HSGW Neighbor Solicitation
D. The address prefix from HSGW Router Solicitation

Answer: B
Explanation:

QUESTION NO: 8

Which two messages are used by Diameter Base Protocol? (Choose two.)

A. Capabilities Exchange Request
B. Capabilities Exchange Answer
C. Device Exchange Request
D. Device Exchange Answer
E. Registration Request
F. Registration Response

Answer: A,B
Explanation:

QUESTION NO: 9

Which two Transport layer protocols are used by Diameter Base Protocol? (Choose two.)

A. TCP
B. UDP
C. DCCP
D. SSDP
E. RSVP
F. SCTP

Answer: A,F
Explanation: