

ISLEVER

640-760

Supporting Cisco Service Provider IP NGN
Operations

DEMO

<https://www.islever.com/640-760.html>

<https://www.islever.com/cisco.html>

For the most up-to-date exam questions and materials, we recommend visiting our website, where you can access the latest content and resources.

QUESTION NO: 1

According to the ITIL® v3 framework, what triggers an incident?

- A. whenever a severity 3 incident is closed
- B. when the problem is identified as urgent
- C. when a problem is discovered during a change window
- D. when an outage is called into a service center

Answer: D

Explanation:

QUESTION NO: 2

According to the ITIL® v3 framework, what is the primary reason for implementing SLAs?

- A. Ensure accurate measurement of response times.
- B. Establish an open line of communication between the customer and the service provider
- C. Reduce network latency.
- D. Provide a legal contract between the customer and the service provider.

Answer: D

Explanation:

QUESTION NO: 3

Each syslog message has a numerical severity level assigned to generate error messages about software or hardware malfunctions. Which of these messages has the highest numeric severity level?

- A. Error
- B. Emergency
- C. Debug
- D. Critical
- E. Alert

Answer: C

Explanation:

QUESTION NO: 4

Which three of these methods can you use to back up a configuration running Cisco IOS Software Release 12.2 Mainline? (Choose three)

- A. SNMP
- B. SFTP
- C. TFTP
- D. KRON
- E. SSH

Answer: A,C,D

Explanation:

QUESTION NO: 5

A router is causing problems in the network and you want to capture as much information as you can before you manually reload or power-cycle the router. What command would you type at the CLI of the router to capture information that would be lost when the router is rebooted?

- A. show crashinfo
- B. show syslog
- C. show tech-support
- D. show stacks
- E. show memory

Answer: C

Explanation:

QUESTION NO: 6

Which three steps are best practices in accurately documenting a network? (Choose three).

- A. Document separate Layer 2 and Layer 3 topologies.
- B. Document Layer 3 topology to include all switches and routers.
- C. Clearly document the port identifiers on all of the links.
- D. Clearly depict different routing domains with appropriate information such as the routing protocol and process number.
- E. Avoid defining router-id commands and loopbacks in the router label.
- F. Use connectivity details of all layers of the OSI model in diagrams.

Answer: A,C,D

Explanation:

QUESTION NO: 7

Which three steps would you use to troubleshoot a performance-related problem in the network core? (Choose three.)

- A. define problem
- B. analyze problem
- C. determine affected users
- D. create action plan
- E. verify service-level requirements

Answer: A,B,D

Explanation:

QUESTION NO: 8

Which two steps are best practices to be followed while documenting a network. (Choose two.)

- A. Use proper icons for different devices in the network.
- B. Use different colors and widths for denoting different links of different bandwidth.
- C. Use same icons for all types of routers and switches in the network.
- D. Avoid defining the router-id in the router label.
- E. Use connectivity details of all layers of the OSI model in diagrams.

Answer: A,B

Explanation:

QUESTION NO: 9

What is the advantage of using a passive monitoring technique?

- A. does not require continuous measurement of traffic types
- B. measures application-specific parameters per traffic classes
- C. identifies issues and bottlenecks before they occur
- D. no interference with live traffic