

ISLEVER

642-523

Securing Networks with PIX and ASA

DEMO

<https://www.islever.com/642-523.html>

<https://www.islever.com/cisco.html>

For the most up-to-date exam questions and materials, we recommend visiting our website, where you can access the latest content and resources.

QUESTION NO: 1

Which of these commands enables IKE on the outside interface?

- A. nameif outside isakmp enable
- B. int g0/0 ike enable (outbound)
- C. isakmp enable outside
- D. ike enable outside

Answer: C

QUESTION NO: 2

Refer to the exhibit. Select the command that will apply this policy map to an interface and the command that will apply it globally on the Cisco ASA. (Choose two.)

```
hostname(config)# class-map inspection_default
hostname(config-cmap)# match default_inspection_traffic
hostname(config)# class-map HTTP_TRAFFIC
hostname(config-cmap)# match port tcp eq 80
hostname(config)# class-map HTTP_PROXY_TRAFFIC_8080
hostname(config-cmap)# match port tcp eq 8080

hostname(config)# policy-map OUTSIDE_POLICY
hostname(config-pmap)# class inspection_default
hostname(config-pmap-c)# inspect http HTTP_TRAFFIC
hostname(config-pmap-c)# inspect http HTTP_PROXY_TRAFFIC_8080
hostname(config-pmap)# class HTTP_TRAFFIC
hostname(config-pmap-c)# set connection timeout tcp 0:10:0
hostname(config-pmap)# class HTTP_PROXY_TRAFFIC
hostname(config-pmap-c)# set connection timeout tcp 0:10:0
```

ActualTests

- A. service-policy policy-map OUTSIDE_POLICY interface outside
- B. service-policy OUTSIDE_POLICY global
- C. policy-map OUTSIDE_POLICY interface outside
- D. service-policy policy-map OUTSIDE_POLICY global
- E. service-policy OUTSIDE_POLICY interface outside
- F. policy-map OUTSIDE_POLICY global

Answer: B,E

QUESTION NO: 3

Refer to the exhibit. What will the adaptive security appliance do if it is configured as shown?

```
regex NEWCLIENT1 NewP2P1
regex NEWCLIENT2 NewP2P2
class-map type regex match-any NEW_P2P
  match regex NEWCLIENT1
  match regex NEWCLIENT2
class-map type inspect http match-all BLOCK_NEW_P2P
  match request header user-agent regex class NEW_P2P
  match request method post
policy-map type inspect http MY_HTTP_MAP
  parameters
    class BLOCK_NEW_P2P
    drop-connection
policy-map WEB_POLICY
  class inspection_default
  inspect http MY_HTTP_MAP
service-policy WEB_POLICY interface inside
```

ActualTests

- A. drop any HTTP connection request that contains the NewP2P1 and NewP2P2 strings and also uses the POST request method
- B. drop any HTTP connection request that contains either the NewP2P1 or the NewP2P2 string, and also uses the POST request method
- C. drop any HTTP connection request that contains either the NewP2P1 or the NewP2P2 string, or that uses the POST request method
- D. drop any HTTP connection request that either contains the NewP2P1 and the NewP2P2 strings, or uses the POST request method

Answer: B

QUESTION NO: 4

Which command configures the Cisco ASA console for SSH access by a local user?

- A. aaa authentication ssh console LOCAL
- B. ssh console username sysadmin password cisco123
- C. ssh username sysadmin password cisco123

D. aaa authentication ssh LOCAL

Answer: A

QUESTION NO: 5

When configuring a crypto ipsec transform-set command, how many unique transforms can a single transform set contain?

- A. two
- B. one
- C. four
- D. three

Answer: A

QUESTION NO: 6

Which of the following statements about the configuration of WebVPN on the Cisco ASA is true for Cisco ASA version 7.2?

- A. WebVPN and Cisco ASDM cannot be enabled at the same time on the Cisco ASA.
- B. WebVPN and Cisco ASDM cannot run on the same interface.
- C. WebVPN and Cisco ASDM can only be enabled at the same time using the command line interface.
- D. WebVPN and Cisco ASDM can both be enabled on the same interface, but must run on different TCP ports.

Answer: D

QUESTION NO: 7

Which of the following statements about adaptive security appliance failover is true?

- A. The Cisco ASA and PIX security appliances support LAN-based and cable-based failover.
- B. The PIX adaptive security appliance only supports LAN-based failover.
- C. The Cisco ASA security appliance only supports cable-based failover.
- D. The PIX adaptive security appliance supports LAN-based and cable-based failover.

Answer: D