ISLEVER

650-473

Implementing Cisco Identity Services Engine Secure Solutions Exam (ISE)

DEMO

https://www.islever.com/650-473.html

https://www.islever.com/cisco.html

For the most up-to-date exam questions and materials, we recommend visiting our website, where you can access the latest content and resources.

QUESTION NO: 1

Which of these is not an Inline Posture node operating mode?

- A. router mode
- B. transparent mode
- C. bridged mode
- D. maintenance mode

Answer: B

Explanation:

QUESTION NO: 2

Which one of the following statements is not a correct statement about posture?

- **A.** CoA is required for WebAuth.
- **B.** Cisco ISE Administrator can create multiple agent profiles.
- **C.** Both simple and compound conditions can be used to construct posture requirements.
- **D.** Wireless posture supports multiple authentication methods.

Answer: C

Explanation:

QUESTION NO: 3

What are the three default behaviors of Cisco ISE with respect to authentication, when a user connects to a switch that is configured for 802.1X, MAB, and WebAuth? (Choose three)

- **A.** MAB traffic uses internal endpoints for retrieving identity.
- **B.** Dot1X traffic uses a user-defined identity store for retrieving identity.
- **C.** Unmatched traffic is allowed on the network.
- **D.** Unmatched traffic is dropped because of the Reject/Reject/Drop action that is configured under Options.
- **E.** Dot1 traffic uses internal users for retrieving identity.

Answer: A,D,E Explanation:

QUESTION NO: 4

The profiling data from network access devices is sent to which Cisco ISE node?

- A. Monitoring node
- B. Administration node
- C. Inline Posture node
- D. Policy Service node

Answer: D Explanation:

QUESTION NO: 5

Which statement is not true about client provisioning (CP)?

- **A.** Cisco ISE manages client provisioning resources for your clients.
- **B.** Client provisioning resources are only provisioned from the ISE Administration node.
- **C.** The remediation timer is a means for clients to remediate themselves.
- D. Client provisioning can only provision the NAC Agent

Answer: D Explanation:

QUESTION NO: 6

Which default action or action should you take when endpoint usage count exceeds license endpoint value?

- A. Bock all traffic, and generate alarms.
- B. Bock all traffic
- **C.** Do not take any action.
- **D.** Do not bock traffic and generate an INFO/WARNING/CRITICAL alarm.

Answer: C Explanation:

QUESTION NO: 7

The authorization policy in the exhibit is using "Multiple Matched Rule Applies" for rule matching.

ProfileA = VLAN attribute 10, DACL= EmptoyeeSanJose

ProfileB = VLAN attribute 20, DACL= Employee. Voice DomainPermission = TRUE

Which statement is correct with regards to the Multiple Matched rule?



- **A.** If both Rule 1 and Rule 2 are matched based on the conditions, the switch will get "VLAN attribute 20, DACL= Employee, Voice DomoinPermission = TRUE".
- **B.** If both Rule 1 and Rule 2 are matched based on the conditions, the switch will get only "VLAN attribute 10, DACL = EmployceSonJose, Voice DomainPermission = TRUE".
- **C.** If both Rule 1 and Rule 2 are matched based on the conditions, the switch will get only "VLAN attribute 10, DACL= EmployeeSanJose".
- **D.** The Multiple Matched rule is not supported in Cisco ISE.

Answer: B Explanation:

QUESTION NO: 8

What is the process for Cisco ISE to obtain a signed certificate from a CA?

- **A.** Generate a CSR; export the CSR to the local file system and send to the CA; download the certificate from the CA. and bind the CA-signed certificate with its private key.
- **B.** Submit a CSR to the CA; download the certificate from the CA" bind the CA-signed certificate with its private key, and import the CA-signed certificate into ISE.
- **C.** Request a certificate from the CA, and import the CA-signed certificate into ISE.
- **D.** Generate a CSR; download the certificate from the CA; bind the CA-signed certificate with its private key, and import the CA-signed certificate into ISE.

Answer: A