

ISLEVER

920-233

NCSS - Nortel VPN Router (Contivity)RIs.6.0

DEMO

<https://www.islever.com/920-233.html>

<https://www.islever.com/nortel.html>

For the most up-to-date exam questions and materials, we recommend visiting our website, where you can access the latest content and resources.

QUESTION NO: 1

Click the Exhibit button.

A remote user has reported that he cannot login to a Contivity.

Given the Contivity 2700 event log shown in the exhibit, what may have caused this problem to occur?

```
03/13/2001 09:28:11 0 Security [13] Session: IPSEC uid invalid -  
authentication failed  
03/13/2001 09:28:11 0 ISAKMP [13] No proposal chosen in message from  
10.0.0.126  
03/13/2001 09:28:11 0 ISAKMP [02] Deleting ISAKMP SA with 10.0.0.126
```

- A. The user name does not exist in any of the enabled authentication methods on the Contivity.
- B. IPSec is not enabled on the Contivity.
- C. There is an encryption type mis-match between the user and server.
- D. There is no active session between the user and the server.

Answer: A

QUESTION NO: 2

You have been tasked to troubleshoot a customer's Contivity network. You log into the Contivity to view information in the routing table and identify UTUNNEL routes. What does the UTUNNEL status information mean?

- A. Client Address Redistribution is enabled.
- B. Access list are enabled.
- C. Route Policy Services are enabled.
- D. The UTUNNEL route is the same as a Static route.

Answer: A

QUESTION NO: 3

Your customer is very concerned about security and wants to encrypt the company data. What encrypts data at the session layer of the OSI model?

- A. SSL
- B. IPSEC
- C. L2TP

D. PPTP

Answer: A

QUESTION NO: 4

A customer is implementing a Contivity 5000. The Contivity must support Data Link Switching, OSPF, and BGP. What are the licensing requirements?

- A. Premium Routing
- B. Advanced Routing
- C. Advanced Routing and BGP
- D. DLSw and Premium Routing

Answer: D

QUESTION NO: 5

Which two key features are supported by the Remote Access Manager? (Choose two.)

- A. Hot-Spot wireless sniffer
- B. VPN Router MultiOS Client integration
- C. Web-UI Configuration
- D. SNMP traps

Answer: A,B

QUESTION NO: 6

Which QoS parameter should you set to prevent too many low-priority users from connecting to a Contivity VPN Router?

- A. Resource Reservation Protocol
- B. Forwarding Priority
- C. Call Admission Priority
- D. DiffServ

Answer: C

QUESTION NO: 7

A customer has two Contivity 5000 gateways installed in its network and wants to use one LDAP server to authenticate clients for both gateways. Which statement is true?

- A. Each gateway may be serviced by the other gateway's internal LDAP server.
- B. Each gateway must be serviced locally by its own internal LDAP server.
- C. Both gateways must be serviced by an external LDAP server.
- D. LDAP cannot be used in this application; RADIUS is the only viable option.

Answer: C

QUESTION NO: 8

A customer wants OSPF routing configured on the company Contivity system. The OSPF routing protocol will be used to manage a large university network made up of several smaller campus networks each with its own OSPF Area. When setting up the OSPF areas, what requirement must you follow when configuring the option on the Contivity system?

- A. The interfaces must be point-to-point, not broadcast.
- B. The Area IDs must be unique.
- C. The Area Integers must be the same.
- D. The interface IP addresses within the OSPF must share a common subnet mask.

Answer: B

QUESTION NO: 9

Which protocol does PPTP use to encapsulate data?

- A. ESP
- B. GRE
- C. L2TP
- D. AH

Answer: B

QUESTION NO: 10

A customer has a Contivity 1750 with VPN tunneling capabilities. The customer wants to enable subscribers to have user tunnel connections to the router. Which parameter must you configure in order to implement user tunnels on a Contivity?