

ISLEVER

# 920-433

Comm Svr 1000 Upgrades to Rls.5.0 for  
Techs, Linux & Apps

DEMO

<https://www.islever.com/920-433.html>

<https://www.islever.com/nortel.html>

For the most up-to-date exam questions and materials, we recommend visiting our website, where you can access the latest content and resources.

---

**QUESTION NO: 1**

A customer has upgraded to Communication Server 1000E RIs. 5.0 and is using the Management Tool NRSM on Linux. In conducting a search for Routing Entries, the engineer is looking for a specific number range. The engineer wants to secure all entries from the entire service domain and identify specific end points where they terminate. What is a more efficient procedure for searching for Routing Entries?

- A. Enter the specific DN type + the entire scope searching.
- B. Enter \*56\* (considered a wild card) + the entire scope searching.
- C. Enter #56# (considered a wild card) + the entire scope searching.
- D. Enter the specific service domain + the entire service domains to specific endpoints.

**Answer: B**

**QUESTION NO: 2**

A customer is upgrading to Communication Server 1000E RIs. 5.0. With this configuration, they will be using all of the Management Features; however, they are currently at Optivity Telephony Manager (OTM) RIs. 2.2. What is the upgrade path for the most current Telephony Manager (TM) offering, and what will occur to the database during the upgrade?

- A. Only an upgrade from OTMRIs. 2.2 to TM RIs. 3.0 is supported, and the database is automatically migrated during the upgrade.
- B. A direct upgrade from OTMRIs. 2.2 to TM RIs. 3.1 is supported, and the database is automatically migrated during the upgrade.
- C. A direct upgrade from OTMRIs. 2.2 to TM RIs. 3.1 is supported, with the database having to manually be migrated during the upgrade.
- D. Only an upgrade from TMRIs. 3.0 to TM RIs. 3.1 is supported, with the database having to be manually migrated during the upgrade.

**Answer: B**

**QUESTION NO: 3**

A customer is upgrading to Communication Server (CS) 1000E RIs. 5.0. The customer wants to utilize TLS for SIP traffic security in their network. What security does TLS provide?

- A. TLS provides audio encryption between SIP clients only.
- B. TLS provides audio encryption between Unistim clients only.
- C. TLS provides signaling encryption between all SIP endpoints.
- D. TLS provides signaling encryption between all system clients.

---

**Answer: C**

**QUESTION NO: 4**

A customer is upgrading to Communication Server 1000E RIs. 5.0. The customer wants to take advantage of Secure Media Exchange (SRTP) so voice conversations are secure. What needs to occur for Media Security to be provided?

- A. IP Phones Phase 1 must be using the DSPs located on the MGC and MC32S cards only.
- B. IP Phones Phase 2 must be using the DSPs located on the Voice Gateway Media Cards only.
- C. IP Phones Phase 0 must be using the DSPs located on the MGC and MC32S cards only.
- D. IP Phones Phase 2 must be using the DSPs located on the MGC and MC32S cards only

**Answer: D**

**QUESTION NO: 5**

A customer has multiple Communication Server (CS) 1000Es. When calls are placed on hold, they want to provide the same music network-wide to their calls. Which configuration is needed for this support?

- A. Network Music is provided only to those calls that are transferred to the music source using Release Link Trunk over H.323.
- B. Music Trunks are installed only on the primary node, connecting to an analog TIE trunk using H.323/SIP virtual trunks. Only calls placed on hold at the primary node will receive this specific music source.
- C. Network Time Protocol (NTP) which is used to synchronize local clocks across the network to a single, accurate, third party NTP server, such as a radio clock.
- D. Music Trunks are installed on the remote nodes and connected back-to-back with an analog TIE trunk, which is auto-terminated to the primary DN of a Network Music Agent. When a music trunk is seized, the call is connected to the Audio Server through an H.323/SIP virtual trunk. A network music path is then established.

**Answer: D**

**QUESTION NO: 6**

A customer is upgrading to Communication Server 1000E RIs. 5.0. During their database configuration, they need to ensure that the Emergency Services for Client Mobility feature is supported, but they are uncertain whether their upgrade supports this application. What prompt(s) should be enabled, and what configuration is needed to ensure this support?

- 
- A. ESA must be disabled. Emergency Response Location (ERL), Emergency Caller Location (ECL) and internal Location Information Service (Package 336) must be programmed.
  - B. ESA Package 329 must be enabled and programmed, allowing the Emergency Response Location (ERL) and Emergency Caller Location (ECL) and internal Location Information Service (Package 336) to be used.
  - C. New System Type 4021 must be activated before the Emergency Response Location (ERL) and Emergency Caller Location (ECL) appear in Web Station.
  - D. The addition of HA Package 410 must be activated before the Emergency Response Location (ERL) and Emergency Caller Location (ECL) appear in Web Station.

**Answer: B**

#### **QUESTION NO: 7**

A customer is upgrading from Communication Server 1000E RIs. 5.0 Standard Availability to Communication Server 1000E RIs. 5.0 High Availability. In addition to a Media Gateway 1000E, what configuration must be in place for this to occur?

- A. A CP-PM and an MGC
- B. A CP-PM CS, an MGC, and package 410 High Availability
- C. A CP-PM CS, CP-PM SS, an MGC, and package 405 GRSEC
- D. A CP-PM CS with either a CP-PM SS, ISP 1100 or COTS VxWorks SS, and an MGC, and package 410 High Availability

**Answer: D**

#### **QUESTION NO: 8**

A customer is upgrading to Communication Server 1000E RIs. 5.0 and needs additional temporary IP User Licenses for controlled load sharing between two systems. Which statement is true regarding the licenses to be ordered and the use of additional IP User Licenses?

- A. No additional licenses need to be ordered. If the customer runs out of IP User Licenses for the 1150E, they can use the Basic IP User Licenses.
- B. Basic IP User Licenses must be ordered. Regular IP Licenses will be used if the temporary license count is exceeded.
- C. Regular IP User Licenses must be ordered. Basic IP User Licenses will be used if the temporary license count is exceeded.
- D. Temporary User Licenses should be ordered. Basic IP or Regular IP User Licenses will be used if the temporary license count is exceeded.