

ISLEVER

# 920-471

Nortel Converged Office CS 1000 RIs. 5.x  
Config & Networking

DEMO

<https://www.islever.com/920-471.html>

<https://www.islever.com/nortel.html>

For the most up-to-date exam questions and materials, we recommend visiting our website, where you can access the latest content and resources.

---

**QUESTION NO: 1**

A customer has an IP Peer Network and has made changes to the dialing plan in the Network Routing Service. Which Database Action option lets you activate changes and run tests without making the changes permanent?

- A. Cutover
- B. Commit
- C. Rollback
- D. Reset and Test

**Answer: A**

**QUESTION NO: 2**

The customer recently implemented IP Peer Networking in a Communication Server 1000 RIs. 5.0 network. The customer now wants to deploy the Geographic Redundancy feature. Which Network Routing Service element must be configured to support Geographic Redundancy?

- A. Branch Office
- B. Collaborative Server
- C. Emergency Services
- D. Network Connection Service

**Answer: D**

**QUESTION NO: 3**

A customer has IP Peer network using only the SIP protocol. Signaling Server 1 hosts the Primary NRS. The customer wants to add an Alternate NRS using Signaling Server 2, which resides at a remote site. Considering the company requirements, which step is required?

- A. Change NRS role of Signaling Server 2 to Active.
- B. Change NRS role of Signaling Server 2 to Alternate.
- C. Change the SIP URI Mapping to Alternate for all nodes.
- D. Change the ENL/DIS switch on Signaling Server 1 to Alternate.

**Answer: B**

**QUESTION NO: 4**

---

You are configuring the Network Routing Service for an H.323 network. Which step is mandatory for all IP Peer Networking scenarios?

- A. Add a Service Domain
- B. Add a Collaborative Server
- C. Implement Geographic Redundancy
- D. Configure the Network Connection Server

**Answer: A**

#### **QUESTION NO: 5**

Which Network Routing Service option lets you view the last database synchronization for the Alternate NRS?

- A. Tools
- B. Reports
- C. Configuration
- D. Administration

**Answer: B**

#### **QUESTION NO: 6**

You have received a work order to add a new endpoint to the Network Routing Service database. Which database schema or view would you use for administrator modifications?

- A. Active
- B. Standby
- C. Passthru
- D. Collaborative

**Answer: B**

#### **QUESTION NO: 7**

You are defining generic settings for the NRS Server. Which is the correct entry or definition for the NRS Server Host name?

- A. Node ID address of the SIP Proxy
- B. ELAN IP address of the Call Server

- 
- C. TLAN IP address of the Primary NRS
  - D. Alias of connected host Signaling Server

**Answer: D**

**QUESTION NO: 8**

During a planned work activity, the customer powered off the Primary Signaling Server on a Communication Server 1000 RIs. 5.0 system. Following the work activity, some IP telephones were unreachable, and they appeared to have old Directory Numbers assigned to them. Which database configuration parameter would you check on the Alternate Signaling Server within the Network Routing Service?

- A. Re-boot the Alternate Signaling Server and invoke the BIOS command.
- B. Verify that the Alternate Signaling Server is defined for Fail-safe situations.
- C. Verify that the Signaling Server is defined as the Alternate Signaling Server.
- D. Verify that the Alternate Gatekeeper is configured for automatic database synchronization.

**Answer: D**

**QUESTION NO: 9**

You are using Element Manager to verify the system configuration before implementing IP Peer Networking. Which element can you configure or modify using Element Manager, assuming a VxWorks platform?

- A. Call Server
- B. Hardware watchdog
- C. Network Connection Service
- D. Basic Input Output System (BIOS)

**Answer: A**

**QUESTION NO: 10**

Which Communication Server 1000 web-based administration application does the Signaling host?

- A. Call Server
- B. NRS Manager
- C. Branch Office