

ISLEVER

920-544

Carrier VoIP Integrated Element Mgmt System
(IEMS) Ops

DEMO

<https://www.islever.com/920-544.html>

<https://www.islever.com/nortel.html>

For the most up-to-date exam questions and materials, we recommend visiting our website, where you can access the latest content and resources.

QUESTION NO: 1

Which feature is part of the alarm count panel?

- A. Alarms with a warning severity are not shown.
- B. A summary of all critical alarms may be obtained.
- C. An annotation may be made from the alarms count panel.
- D. Alarms may be acknowledged from the alarms counts panel.

Answer: B

QUESTION NO: 2

Under which of the following in the topology tree is the Alarms node found?

- A. Inventory
- B. Performance
- C. Network Events
- D. Fault Management

Answer: D

QUESTION NO: 3

Which action may be used to display the icon of the managed object that is the source of a given alarm?

- A. From the alarm popup menu, select Show Map.
- B. Double-click on the alarm and select Show Map Detail.
- C. From the alarm popup menu, select Show Managed Object.
- D. Double-click on the alarm and select Managed Object Detail.

Answer: A

QUESTION NO: 4

Which of the following is true for events that are received from devices that are not part of Integrated EMS inventory database?

- A. The IEMS will temporarily add the source device to the inventory.

-
- B. These events have a source field value of Unrecognized Device.
 - C. The IEMS application assigns these events a logkey value of IEMS601.
 - D. The IEMS application will propagate these events to alarms with a minor severity.

Answer: C

QUESTION NO: 5

Which protocol is used to establish an Operator Client session from the IEMS into the Multiservice Data Manager?

- A. SSH
- B. Telnet
- C. HTTPS
- D. SNMPv3

Answer: C

QUESTION NO: 6

Which Network Element requires its GUI element manager application to be installed on the client?

- A. STORM
- B. Call Agent
- C. ERS 8600
- D. MSS 15000

Answer: C

QUESTION NO: 7

Which statement is true for performing IEMS application upgrades in a dual server (HA) environment?

- A. During the upgrade, neither server is in service.
- B. The upgrade must first be performed on the active server.
- C. A failover must not be performed until both servers are upgraded.
- D. Upgrades are performed on the standby server, while the active server is in service.

Answer: D

QUESTION NO: 8

How many simultaneous sessions of each of the four supported Northbound fault streams are supported?

- A. 2
- B. 4
- C. 6
- D. 8

Answer: C

QUESTION NO: 9

Which two must be provisioned on the IEMS in order to set up a Northbound SNMP fault stream? (Choose two.)

- A. the directory of the SNMP trap destination host (Managerdir)
- B. the MAC address of the SNMP trap destination (Managemac)
- C. the IP address of the SNMP trap destination host (Managerhost)
- D. the port number of the SNMP trap destination host (Managerport)

Answer: C,D

QUESTION NO: 10

Which Servman command can be issued to start the IEMS server application?

- A. start IEMS
- B. servstart IEMS
- C. startserv IEMS
- D. servman start IEMS

Answer: B

QUESTION NO: 11

Which steps from the IEMS menu are required to launch the alert filter configuration tool?