

ISLEVER

922-020

MCS 5100 Ris.4.0 Installation &
Commissioning

DEMO

<https://www.islever.com/922-020.html>

<https://www.islever.com/nortel.html>

For the most up-to-date exam questions and materials, we recommend visiting our website, where you can access the latest content and resources.

QUESTION NO: 1

What is the purpose of the RTP protocol in a Multimedia Communication Server (MCS) 5100 RIs. 4.0 network?

- A. to transport real-time media streams across a packet network
- B. to provide a means of sharing session data between endpoints
- C. to provide a service-enabling protocol for real-time multimedia sessions
- D. to control signaling between the Session Manager and the RTP Media Portal

Answer: A

QUESTION NO: 2

Where is the Unified Network IP Stimulus (UNISim) protocol used in a Multimedia Communication Server (MCS) 5100 RIs. 4.0 network?

- A. on ISDN PRI connections to the PSTN
- B. between IP Phones and the IP Client Manager (IPCM)
- C. between the Provisioning Client and an external SIP Gateway
- D. between the System Management Console and the Session Manager

Answer: B

QUESTION NO: 3

A customer is deploying a new Multimedia Communication Server (MCS) 5100 RIs. 4.0 system.

While editing the installprops.txt file, what IP Address needs to be configured?

- A. the service logical IPaddress
- B. the floating service IPaddress
- C. the machine logical IP address
- D. the Dynamic Host Configuration Protocol (DHCP) server IP address

Answer: C

QUESTION NO: 4

The technician is viewing a command typed from a PuTTY terminal that verifies the IP addressing for the System/Accounting Manager. If the interface eth0 is not UP (it is unavailable), to which

interface would the machine logically attach itself?

- A. lo0
- B. eth1
- C. dmfe0
- D. dmfe0:2

Answer: B

QUESTION NO: 5

A support engineer is preparing to install a Multimedia Communication Server (MCS) 5100 RIs. 4.0 system. The MCS 5100 servers have all been physically installed and cabled to the In-Reach Terminal Server. Which information should you configure on the In-Reach Terminal Server to allow access to the MCS 5100 servers through it?

- A. Define the IP address for each MCS 5100 server.
- B. Define the IP address for the Management Console PC.
- C. Define the port speed for each MCS 5100 server connection.
- D. Define the IP Address port number to which the MCS 5100 server is connected.

Answer: C

QUESTION NO: 6

An administrator is in the process of installing the Multimedia Communication Server (MCS) 5100 RIs. 4.0 software. The Management Console Graphical User Interface (GUI) has successfully launched. What is the next step in the installation process for a four-server system?

- A. Deploy the Session Manager.
- B. Deploy the Accounting Manager.
- C. Deploy the Provisioning Manager.
- D. Verify the deployment of the System Manager.

Answer: B

QUESTION NO: 7

During the deployment of a four-server Multimedia Communication Server (MCS) 5100 RIs. 4.0 system, the System Management Console application has been launched. Before uploading the license key, which components are deployed and running by default?

-
- A. the System Manager and a Database instance
 - B. the Session Manager and the Accounting Manager
 - C. the System Manager and the Provisioning Manager
 - D. the Database Manager and the Accounting Manager

Answer: A

QUESTION NO: 8

A customer is verifying the availability of the Ethernet interface on the Prov / IP Client Manager server during the installation of a new Multimedia Communication Server (MCS) 5100 Rls. 4.0 four-server system. An issue is encountered, and the documentation states to use the `ifconfig -a` command. How will this command help to determine the cause and help resolve it?

- A. It will restart all active Ethernet interfaces. If an interface has failed, it will re-activate all Ethernet interfaces.
- B. It will show the IP addresses and status of all Ethernet interfaces. This information will help determine if there is a problem with the Ethernet interfaces.
- C. It will reload the configuration for all Ethernet interfaces. If a change has been made but not loaded, this command ensures that the change is loaded.
- D. This command will show from which configuration file the Ethernet interfaces were loaded. This information will help determine if the proper configuration was used.

Answer: B

QUESTION NO: 9

A support engineer is in the process of executing the Multimedia Communication Server (MCS) 5100 Rls. 4.0 software load in a four-server installation. The `./mcpInstall.pl` script is successfully installed.

What is the next step in the software installation process?

- A. Add and configure the Accounting Module.
- B. Install and launch the IPCM on the System Manager.
- C. Deploy the initial database load on the Database Manager.
- D. Launch the Management Console on the management PC.