# C2040-408

IBM Notes and Domino 9.0 Social Edition
Application Development Update

DEMO

https://www.islever.com/c2040-408.html
https://www.islever.com/ibm.html

**QUESTION NO: 1**

How would a developer enable partial refresh using a Dynamic Content control?

**A.** partialEvents="true"
**B.** partialRefreshMode="true"
**C.** No action needed. By default, partial refresh is enabled.
**D.** getComponent("dynContent").setRefreshMode("Partial")

**Answer: A**
**Explanation:**

**QUESTION NO: 2**

Sam is creating a mobile application using the Mobile controls. When a user opens a page from a view, she would like the view page to fade in when the user returns to it.  How can she accomplish this?

**A.** On the page heading control, Sam should set the transition

**Answer: A**
**Explanation:**

**QUESTION NO: 3**

What does setting the expandLevel property of a Navigator control to "0" do when the expandable property is set to "true"?

**A.** expands all the Navigator control levels
**B.** expands the first (index 0) Navigator child node
**C.** makes the Navigator control show only the parent levels
**D.** prevents the Navigator from displaying a twisty on levels that can be expanded

**Answer: C**
**Explanation:**

**QUESTION NO: 4**

The simpleValuePicker data provider of the Value Picker control supports which kind of data?

**A.** .Net Matrix
**B.** JavaScript Arrays
**C.** @PickerDataSource
**D.** Direct REST API calls

**Answer: B**
**Explanation:**

**QUESTION NO: 5**

Richard wants to allow his users to select names from either of two views using the Name Picker control. How can he do this?

**A.** Richard can use a single Name Picker with two dominoViewNamePicker dataProviders.
**B.** Richard will need to add two Name Pickers, each using a dominoViewNamePicker dataProvider.
**C.** Richard will need to use a beanNamePicker dataProvider to merge the contents of the two views for a single Name Picker.
**D.** Richard can use a single Name Picker with a namePickerAggregator dataProvider. He can add two dominoViewNamePicker dataProviders tothe namePickerAggregator.

**Answer: D**
**Explanation:**

**QUESTION NO: 6**

Which property of viewStateBean should be used to restore the state of a view saved by a Pager Save State control?

**A.** restoreState
**B.** returnViewState
**C.** restoreViewState
**D.** returnStoredState

**Answer: A**
**Explanation:**

**QUESTION NO: 7**

What does the disableHideRow property provide on the Data View control?

**A.** The property automatically shows the details facet and does not allow the user to hide the detail.
**B.** The property automatically shows response documents and does not allow the user to hide them.
**C.** The property does not allow the user to hide the detail, but requires expandedDetail="true" to be set.
**D.** The property does not allow the user to hide response documents, but requires collapsibleRows="true" to be set.

**Answer: A**
**Explanation:**

**QUESTION NO: 8**

The Extension Library provides a Dialog control. What languages can be used to launch the Dialog?

**A.** Client-Side JavaScript and Simple Action
**B.** Server-Side JavaScript and Simple Action
**C.** Client-Side JavaScript and Server-Side JavaScript
**D.** Client-Side JavaScript, Server-Side JavaScript, and Simple Action

**Answer: C**
**Explanation:**

**QUESTION NO: 9**

Joshua is using the Dojo List Text Box control to display values of the department code for the internal forum XPages application. Joshua is planning to use these values:  Research & Development (rd), Marketing (mkt), Engineering (eng), and Human Resources (hr).  He needs to store the department code in the dept field but wants to display a readable label to the user. How can Joshua configure the Value Picker control to display the correct information in the Dojo List Text Box control and store the department code in the underlying field?