

ISLEVER

DEV-501

Apex and Visualforce Controllers Exam

DEMO

<https://www.islever.com/dev-501.html>

<https://www.islever.com/salesforce.html>

For the most up-to-date exam questions and materials, we recommend visiting our website, where you can access the latest content and resources.

QUESTION NO: 1

The email publisher lets support agents who use Case Feed compose and send email messages to customers. You can customize this publisher to support email templates and attachments. This component can only be used in organizations that have Case Feed and Email-to-Case enabled. Ext JS versions less than 3 should not be included on pages that use this component.

- A. apex:pageBlock
- B. apex:define
- C. apex:component
- D. apex:emailPublisher

Answer: D

Explanation:

QUESTION NO: 2

An area of a Visualforce page that demarcates which components should be processed by the Force.com server when an AJAX request is generated. Only the components in the body of the <apex:actionRegion> are processed by the server, thereby increasing the performance of the page.

- A. apex:outputLabel
- B. apex:actionRegion
- C. apex:facet
- D. apex:emailPublisher

Answer: B

Explanation:

QUESTION NO: 3

A link that executes an action defined by a controller, and then either refreshes the current page, or navigates to a different page based on the PageReference variable that is returned by the action. An <apex:commandLink> component must always be a child of an <apex:form> component.

To add request parameters to an <apex:commandLink>, use nested <apex:param> components.

- A. apex:dataList

-
- B. apex:enhancedList
 - C. apex:commandLink
 - D. apex:include

Answer: C

Explanation:

QUESTION NO: 4

A timer that sends an AJAX update request to the server according to a time interval that you specify. The update request can then result in a full or partial page update. You should avoid using this component with enhanced lists.

- A. apex:dataList
- B. apex:actionPoller
- C. apex:inlineEditSupport
- D. apex:image

Answer: B

Explanation:

QUESTION NO: 5

A single column in a table. An <apex:column> component must always be a child of an <apex:dataTable> or <apex:pageBlockTable> component.

Note that if you specify an sObject field as the value attribute for an <apex:column>, the associated label for that field is used as the column header by default. To override this behavior, use the headerValue attribute on the column, or the column's header facet.

- A. apex:inputField
- B. apex:column
- C. apex:inputText
- D. apex:insert

Answer: B

Explanation:

QUESTION NO: 6

An HTML input element of type hidden, that is, an input element that is invisible to the user. Use this component to pass variables from page to page.

- A. apex:inputHidden
- B. apex:actionPoller
- C. apex:pageBlockSectionItem
- D. apex:enhancedList

Answer: A

Explanation:

QUESTION NO: 7

This tag acts as a placeholder for your dynamic Apex components. It has one required parameter—component Value—which accepts the name of an Apex method that returns a dynamic component.

The following Visualforce components do not have dynamic Apex representations:

<apex:actionRegion>

<apex:attribute>

<apex:component>

<apex:componentBody>

<apex:composition>

<apex:define>

<apex:dynamicComponent>

<apex:flash>

<apex:inputFile>

<apex:include>

<apex:insert>

<apex:pageMessage>

<apex:pageMessages>