

ISLEVER

E20-361

Network Attached Storage (NAS)
Implementation Exam

DEMO

<https://www.islever.com/e20-361.html>

<https://www.islever.com/emc.html>

For the most up-to-date exam questions and materials, we recommend visiting our website, where you can access the latest content and resources.

QUESTION NO: 1

Which state should a Virtual Data Mover be in before it is fully functional?

- A. Loaded
- B. Mounted
- C. PermUnloaded
- D. TempUnloade

Answer: A

QUESTION NO: 2

A NAS solution that includes high availability and network connections that are always available is required. The Ethernet switch is made by Typhoon Data Networks and is IEEE channel compliant.

Which EMC. NAS networking solution must be implemented?

- A. FastEtherChannel
- B. HSRP
- C. LACP
- D. VLAN

Answer: C

QUESTION NO: 3

Which two objects are associated together to provide name resolution?

- A. Hostname and IP address
- B. Hostname and MAC.address
- C. Hostname and network port
- D. Hostname and operating system version number

Answer: A

QUESTION NO: 4

How can a CIFS share be hidden from network browsing?

- A. Append the share name with a "\$"
- B. Edit the permissions of the share and select "Deny for Browsing"

C. Edit the share's properties and select "Hidden"

D. Prefix the share name with a "."

Answer: A

QUESTION NO: 5

A UNIX client mounts a file system presented by the Celerra. Which name resolution is valid?

A. CIFS

B. NFS

C. NIS

D. WINS

Answer: C

QUESTION NO: 6

Which remote console tool uses the following recommended attributes when connecting to a Celerra?

Attributes:

19200 bits per second, 8 data bits, no parity, 1 stop bit, No flow control

A. HyperTerminal

B. Init Wzard

C. PuTTY

D. WinSCP

Answer: A

QUESTION NO: 7

Which type of NS installation requires the user to acquire the public IP addresses of the storage SPs, username, password, and VSAN name prior to the install?

A. Direct-connect gateway install

B. Manual integrated install

C. Simplified gateway install

D. Simplified integrated install

Answer: C

QUESTION NO: 8

In the Celerra NSX series models, how does the Control Station communicate and monitor the blades?

- A. Ethernet switch link
- B. Ethernet switch link and serial connections
- C. Fibre Channel connections
- D. Serial connections

Answer: A

QUESTION NO: 9

A new customer is interested in learning about block-level storage over IP. Which deployment models can be used with the Celerra?

- A. Bridging, Extension, Local
- B. Extension, Local, Remote
- C. Native, Bridging, Extension
- D. Native, Remote, Bridging

Answer: C

QUESTION NO: 10

Which solution offers customers with data targeted TLUs a backup infrastructure where only commands pass over the corporate network?

- A. Backup using NDMP
- B. Backup using server_archive
- C. Network backup from a CIFS client
- D. Network backup from an NFS client

Answer: A

QUESTION NO: 11