

ISLEVER

E20-651

Networked Storage-SAB Installation and
Troubleshooting Exam

DEMO

<https://www.islever.com/e20-651.html>

<https://www.islever.com/emc.html>

For the most up-to-date exam questions and materials, we recommend visiting our website, where you can access the latest content and resources.

QUESTION NO: 1

Which two [2] tasks must be performed on the CLARiiON before configuring PowerPath?

- A. Set the failover mode to 1
- B. Configure VolumeLogix
- C. Configure ArrayCompath
- D. SelectPowerPath
- E. Create Storage groups

Answer: A,C

QUESTION NO: 2

Which addressing does EMC recommend when using persistent binding?

- A. Port and Node World Wide Name Addressing
- B. Port (FC) Addressing
- C. Node World Wide Name Addressing
- D. Port World Wide Name Addressing

Answer: D

QUESTION NO: 3

Which Protocol is characterized by distance, connectivity and speed?

- A. Escon
- B. SCSI
- C. Fibre
- D. Bus & Tag

Answer: C

QUESTION NO: 4

How would you safely change between the active and standby CTP cards?

- A. Unscrew the active CTP and remove it from the backplane.
- B. Unscrew the Standby CTP and remove it from the backplane.
- C. Right mouse click on either the active or standby CTP and select switchover.
- D. Left mouse click on the standby CTP and select Switchover.

Answer: C

QUESTION NO: 5

Which class of service is used for communication across ISLs?

- A. Class F
- B. Class I
- C. Class D
- D. Class B

Answer: A

QUESTION NO: 6

Which command must be used to change path states in PowerPath 3.0 from an active to inactive state?

- A. powermt set state=active hba=hba#
- B. powermt set mode=standby hba=hba#
- C. powermt set policy=inactive hba=hba#
- D. powermt set status=active hba=hba#

Answer: B

QUESTION NO: 7

The SAN-OS consists of which two [2] images?

- A. Loader image
- B. Bootflash image
- C. Kickstart image
- D. Bios image
- E. System image

Answer: C,E

QUESTION NO: 8

What would be the result of running the System Switchover HA command line command on a MDS Director?

-
- A. Reverts the switch settings to perform the defaultstateful switchover the next time the switchover occurs
 - B. Restores the default switchover settings
 - C. Configures the switch to perform a stateless switchover the next time a switchover occurs

Answer: A

QUESTION NO: 9

What happens when the SAN Manager host discovers the SAN?

- A. New Production Hosts are connected to the switch.
- B. Directly connected switches are rebooted.
- C. New records are added to the VCMDB.
- D. Zoning information is added toFibreZone database.

Answer: D

QUESTION NO: 10

Which command line interface command will take you to the configuration prompt?

- A. ctrl c
- B. config c
- C. config t
- D. config r
- E. ctrl t

Answer: C

QUESTION NO: 11

Click the Exhibit button.

Which version of firmware is the switch running?