

ISLEVER

# GB0-180

Huawei Certified Network Engineer

DEMO

<https://www.islever.com/gb0-180.html>

<https://www.islever.com/huawei.html>

For the most up-to-date exam questions and materials, we recommend visiting our website, where you can access the latest content and resources.

---

**QUESTION NO: 1**

The tag header of IEEE 802.1Q varies according to the medium used. According to IEEE802.1Q standard, the tag is embedded in( )

- A. Not at fixed place
- B. Between the source MAC address and destination MAC address
- C. After the source MAC address and the destination MAC address
- D. Before the source MAC address and destination MAC address

**Answer: C**

**QUESTION NO: 2**

The advantages of using access control list include:

- A. Ensure the access by valid users, and refuse some unwished accesses
- B. Make sure all the users of enterprise private network can access Internet
- C. The administrator can differentiate the services in light of time
- D. Through the configuration of access control list, restrict the network flow by filtering certain packet

**Answer: A,C,D**

**QUESTION NO: 3**

While configuring the Frame Relay network with Huawei Quidway routers and Cisco routers, how should you configure the link encapsulation format of Huawei routers? (Assuming that Cisco routers adopt default encapsulation format)

- A. ietf
- B. Q.933a
- C. ansi
- D. nonstandard

**Answer: D**

**QUESTION NO: 4**

IP is considered as an unreliable protocol, because it can NOT ensure that the packet will be transmitted to the destination correctly.

- 
- A. False
  - B. True

**Answer: B**

**QUESTION NO: 5**

Which of the following are point-to-point link layer protocols:

- A. ATM
- B. X.25
- C. PPP
- D. HDLC

**Answer: C,D**

**QUESTION NO: 6**

The broadcast address of 10.1.0.1/17 is

- A. 10.1.128.255
- B. 10.1.127.255
- C. 10.1.126.255
- D. 10.1.63.255

**Answer: B**

**QUESTION NO: 7**

Access control list is applicable to:

- A. None of the above
- B. Only IPX network
- C. Only IP network
- D. All networks, such as IP and IPX

**Answer: D**

**QUESTION NO: 8**

---

Asynchronous serial port can be configured in:

- A. Leased line mode
- B. Voice access mode
- C. PRI access mode
- D. Dial-up mode

**Answer: A,D**

**QUESTION NO: 9**

The IP address, whose first octet begins with binary 1110, is ( ) address

- A. Class A
- B. Class D
- C. Class B
- D. Class C

**Answer: B**

**QUESTION NO: 10**

What is the meaning of the number "7" in the command "fr map ip 10.1.1.1 dlci 7 broadcast"?

- A. The number of local logic channel
- B. The number of node at the opposite end
- C. The number of local DLCI
- D. The number of interface at the opposite end

**Answer: C**

**QUESTION NO: 11**

When V.24 cable is working in asynchronous mode, which of the following link layer encapsulation protocols can be adopted?

- A. X.25
- B. FR
- C. PPP
- D. HDLC

**Answer: C**