

ISLEVER

GB0-183

HuaWei-3Com Certificated

DEMO

<https://www.islever.com/gb0-183.html>

<https://www.islever.com/huawei.html>

For the most up-to-date exam questions and materials, we recommend visiting our website, where you can access the latest content and resources.

QUESTION NO: 1

Frame Relay adopts () as the switching method.

- A. Routing
- B. Circuit switching
- C. Fast switching
- D. Packet switching

Answer: D

QUESTION NO: 2

Two routers are in back-to-back connection with the following configuration. Can they communicate with each other?

```
[Router1]display current-configuration
```

```
#
```

```
sysname Router1
```

```
#
```

```
FTP server enable
```

```
#
```

```
I2tp domain suffix-separator @
```

```
#
```

```
fr switching#
```

```
radius scheme system
```

```
#
```

```
domain system
```

```
#
```

```
local-user admin
```

```
password cipher
```

```
.]@USE=B,53Q=^Q`MAF4<<"TX$_S#6.NM(0=0\)*5WWQ=^Q`MAF4<<"TX$_S#6.N
```

```
service-type telnet terminal
```

```
level 3
```

```
service-type ftp
```

```
#
```

```
interface Aux0
```

```
async mode flow
```

```
#
```

```
interface Ethernet0/0
```

```
ip address dhcp-alloc
```

```
#
```

```
interface Ethernet0/1
```

```
ip address dhcp-alloc
#
interface Serial0/0
link-protocol fr
fr interface-type dce
#
interface Serial0/0.1 p2p
fr dlci 20
ip address 10.0.0.1 255.255.255.0
#
interface NULL0
#
user-interface con 0
user-interface aux 0
user-interface vty 0 4
authentication-mode none
user privilege level 3
#
return
[Router2]display current-configuration
#
sysname Router2
#
FTP server enable
#
l2tp domain suffix-separator @
#
radius scheme system
#
domain system
#
local-user admin
password cipher
.]@USE=B,53Q=^Q`MAF4<<"TX$_S#6.NM(0=0\)*5WWQ=^Q`MAF4<<"TX$_S#6.N
service-type telnet terminal
level 3
service-type ftp
#
interface Aux0
async mode flow
#
interface Ethernet0/0
```

```
ip address dhcp-alloc
#
interface Ethernet0/1
ip address dhcp-alloc
#
interface Serial0/0
clock DTECLK1
link-protocol fr
#
interface Serial0/0.1 p2p
fr dlci 20
ip address 10.0.0.2 255.255.255.0
#
interface NULL0
#
user-interface con 0
user-interface aux 0
user-interface vty 0 4
authentication-mode none
user privilege level 3
#
return
```

A. Yes

B. No

C. No decision can be made, for there is not enough information.

Answer: A

QUESTION NO: 3

Encapsulation means that the network node packets the data to be transmitted with a specific protocol header before transmission, sometimes it will add some information at the tail of the data unit.

A. True

B. False

Answer: A

QUESTION NO: 4