ISLEVER

GB0-363

Designing Enterprise-level Networks

DEMO

https://www.islever.com/gb0-363.html
https://www.islever.com/huawei.html

QUESTION NO: 1

Which of the following descriptions about dynamic routing protocol is correct? ( )

A. The fundamentals ofRIPng are the same as those of RIP, but RIPng speeds up convergence compared with RIP.
B. The packet format of OSPFv3 is the same as that of OSPF, but OSPFv3 can support IPv6.
C. MBGP is the unique EGP routing protocol in the IPv6 network.
D. IS-ISsupports multiple protocols so that it can support IPv6 without any modification.

Answer: C

QUESTION NO: 2

We usually do not choose the equipment with key module redundancy to backup at the access layer. And dual-uplink backup should be used instead of dual-system backup.

A. True
B. False

Answer: A

QUESTION NO: 3

We usually choose the equipment with key module redundancy to backup at the convergence layer. Dual-uplink backup and dual-system backup should be used. Ring topology can be adopted connecting the convergence layer devices.

A. True
B. False

Answer: A

QUESTION NO: 4

The equipment with carrier-class reliability refers to the equipment that supports large capacity, non-stop running, key module redundancy, and high stability.

A. True
B. False

Answer: A

QUESTION NO: 5

VPNs that provide data encryption include IPSec VPN, SSL VPN, DVPN 1.0 and DVPN 2.0.

A. True
B. False

Answer: B

QUESTION NO: 6

Which of the following descriptions about VPN is correct? ( )

A. VPN indicates that the user leases a line by itself and the line shall be secure and separated from the public network completely and physically.
B. VPN refers to a temporary and secure connection established by the user over the public network.
C. VPN cannot provide information authentication or identity authentication.
D. VPN provides identity authentication only and does not offer data encryption.

Answer: B

QUESTION NO: 7

The security services in the Open System Interconnection security architecture include ( ) and anti-DoS.

1) Authentication
2) Access control
3) Data privacy service
4) Data integrity service

A. 1) and 2)
B. 1), 2) and 3)
C. 2) and 4)
D. 1), 2), 3) and 4)

Answer: D

QUESTION NO: 8

During the IP address planning for an enterprise network, we should use the private addresses in principle. In case of insufficiency of the private address space, we can use the public addresses as long as NAT is applied for Internet access.

A. True
B. False

Answer: B

QUESTION NO: 9

Which of the following should be taken into consideration during the IP planning? ( )

A. Uniqueness
B. Continuity
C. Expandability
D. Saving IP address

Answer: A,B,C,D

QUESTION NO: 10

If the external path cost of the imported external route is comparable with the internal path cost of OSPF, or the internal path cost of OSPF can influence the selection of the egresses to reach the external network, the type of the imported external route should be set to Type 2.

A. True
B. False

Answer: B

QUESTION NO: 11

If the data link layer protocol in the OSPF P2P network is PPP, two OSPF routers whose interface addresses are in different subnets can still establish adjacency and learn the routing information correctly.

A. True
B. False