

I S L E V E R

H12-211

HCNA-HNTD (Huawei Certified Network Associate - Huawei Network Technology and Device)

DEMO

<https://www.islever.com/h12-211.html>

<https://www.islever.com/huawei.html>

For the most up-to-date exam questions and materials, we recommend visiting our website, where you can access the latest content and resources.

QUESTION NO: 1

An administrator currently manages AR2200 devices in the network through a single password, however the company wishes to introduce another two administrators and provide unique user credentials and privilege levels for telnet access to the network devices. What action can be taken? (Choose three)

- A. Configure three users under the AAA-view, and assign each a different password.
- B. The authentication mode must be changed to AAA.
- C. Each administrator must be assigned a privilege level.
- D. A public IP address must be assigned to each user for telnet access

Answer: A,B,C

Explanation:

QUESTION NO: 2

Which of the following authentication methods are supported for Telnet users? (Choose three)

- A. Password authentication
- B. AAA local authentication
- C. MD5 authentication
- D. No authentication

Answer: A,B,D

Explanation:

QUESTION NO: 3

Which authentication modes does AAA support? (Choose three).

- A. None
- B. Local
- C. Radius
- D. 802.1X

Answer: A,B,C

Explanation:

QUESTION NO: 4

[RTA]aaa

[RTA-aaa]domain huawei

[RTA-aaa-domain-huawei]authentication-scheme au1

[RTA-aaa-domain-huawei]authentication-scheme au2

Refer to the configuration output. RTA has been configured using AAA as shown, and associated with the “huawei” domain. For users in the huawei domain, which authentication-scheme will be used

- A. au1
- B. au2
- C. au1 will be used. When au1 is deleted, users will use au2
- D. au2 will be used. When au2 is deleted, users will use au1

Answer: B

Explanation:

QUESTION NO: 5

A user accesses a server supporting AAA, for which the authorization mode on the AAA server has been configured using the command “authorization-mode hwtacacs if-authenticated”. Which of the following statements regarding this command are true? (Choose three).

- A. If the hwtacacs server fails to respond, the user will be authenticated using local authentication.
- B. If the hwtacacs server fails to respond, the user will be authenticated using remote authentication.
- C. If the hwtacacs server fails to respond, the user will bypass authentication.
- D. The hwtacacs server will authorize the user.

Answer: A,B,D

Explanation:

QUESTION NO: 6

Which of the following descriptions regarding eSight is not correct?

-
- A. eSight is used to monitor and manage enterprise networks.
 - B. eSight supports only Huawei devices
 - C. eSight supports WLAN management and monitoring of hotspot coverage.
 - D. eSight supports the backup of configuration files and network traffic analysis.

Answer: B

Explanation:

QUESTION NO: 7

What of the following statements is correct regarding access control list types and ranges?

- A. A basic ACL value ranges from 1000-2999
- B. An advanced ACL value ranges from 3000-4000
- C. A layer 2 ACL value ranges from 4000-4999
- D. An interface ACL value ranges 1000-2000

Answer: C

Explanation:

QUESTION NO: 8

Which of the following parameters is not used by Advanced ACL?

- A. Source interface
- B. Destination port number
- C. Protocol number
- D. Time-range

Answer: A

Explanation:

QUESTION NO: 9

```
[RTA]acl 2001
```

```
[RTA-acl-basic-2001]rule permit source 10.0.1.0 0.0.0.255
```

```
[RTA-acl-basic-2001]rule deny source 10.0.1.0 0.0.0.255
```