

ISLEVER

# HP0-J44

Advanced SAN Solutions

DEMO

<https://www.islever.com/hp0-j44.html>

<https://www.islever.com/hp.html>

For the most up-to-date exam questions and materials, we recommend visiting our website, where you can access the latest content and resources.

---

**QUESTION NO: 1**

When considering the cabling of a new SAN environment with 8Gb/s switches, what is the maximum distance per cable segment using OM2 fiber optic cables?

- A. 50 meters
- B. 150 meters
- C. 380 meters
- D. 500 meters

**Answer: A**

**QUESTION NO: 2**

While designing the SAN to meet your customer's throughput requirements, you need to configure several 4Gb/s B-Series SAN switches with inter-switch links. What is the maximum throughput available using a trunk group between 2 switches?

- A. 8Gb/s
- B. 16Gb/s
- C. 32Gb/s
- D. 64Gb/s

**Answer: C**

**QUESTION NO: 3**

What must you consider before you merge an old fabric with a new SAN implementation?

- A. Active array controller ports must be taken offline to allow both fabrics to merge.
- B. Zone configurations must be disabled on the existing fabrics.
- C. New switches must be set to the same domain ID as the existing switches.
- D. Each switch in the merged fabric must have a unique domain ID.

**Answer: D**

**QUESTION NO: 4**

During a SAN switch assessment on a B-series switch, a SAN architect notices that the switch is partitioned in a set of logical switches. What is the name of this feature?

- A. Inter VSAN Routing

- 
- B. Transparent Routing
  - C. Virtual Fabric
  - D. VSAN

**Answer: C**

**QUESTION NO: 5**

Which HP tool can be used to validate the integrity of your customer's current SAN environment prior to a SAN upgrade?

- A. HPStorageWorks SAN Validation
- B. HPStorageWorks SAN Sizer
- C. HPStorageWorks SAN Designer
- D. HPStorageWorks Essentials SAN Visibility

**Answer: D**

**QUESTION NO: 6**

When considering a proof of concept model for a customer with a Customer Relation Database (CRM) environment requiring high bandwidth, which size do you expect for the majority of I/O requests?

- A. less than 8K
- B. less than 100k
- C. greater than 1MB
- D. greater than 100k

**Answer: D**

**QUESTION NO: 7**

When designing a solution for a customer, there are different ways of looking at or viewing the SAN architecture that is part of that solution. What are two of the four SAN architecture views? (Select two.)

- A. Business view
- B. SAN functional view
- C. Storage centric view
- D. Stakeholder view

---

E. SAN switch view

**Answer: A,B**

**QUESTION NO: 8**

What are the primary responsibilities of the SAN architect? (Select three.)

- A. Ensuring data availability
- B. Solving revision conflicts
- C. Solving management problems
- D. Ensuring data protection
- E. Solving SAN scalability issues
- F. Ensuring database consistency or validity

**Answer: A,D,E**

**QUESTION NO: 9**

Which blocksize should you choose for a profile requiring performance-critical random access applications?

- A. 2,048 bytes.
- B. 4,096 bytes
- C. 8,192 bytes
- D. 16,384 bytes

**Answer: A**

**QUESTION NO: 10**

Continuous Access XP software products allow host-independent, real-time, remote data mirroring between XP disk arrays. If you are designing a solution that requires no performance impact on the host application, but the link between sites is not necessarily highly available, what is the best choice?

- A. CA for XP Sync
- B. CA for XPAsync
- C. CA for XP Journal
- D. CA for XP Link Extension