ISLEVER

HP0-J46

Designing and Implementing HP Enterprise Backup Solutions

DEMO

https://www.islever.com/hp0-j46.html

https://www.islever.com/hp.html

For the most up-to-date exam questions and materials, we recommend visiting our website, where you can access the latest content and resources.

Exam A

QUESTION 1

Which type of deduplication technology is implemented in the VLS9000 and VLS12000 EVA gateway?

- A. post-processing
- B. chunk-based
- C. hash-based
- D. in-line

Correct Answer: A Section: (none)

QUESTION 2

When design a backup solution with a D2D4000, how much time should you allow for the housekeeping task to complete per 1TB of dats?

- A. 30 min
- B. 2 hrs
- C. 3.5 hrs
- D. 5hrs

Correct Answer: D Section: (none)

QUESTION 3

Whick service deployments are included in HP Installation and Starup Service for an HP StorageWorks MSL tape library? (Selectg two)

- A. Configuration of up to 2 SAN hosts and only one server per OS type
- B. configuration of up to 5 SAN hosts
- C. installation of the crosslink Kit option
- D. installation and verification of an MSL Encryption Kit
- E. instalaltion, licensing and configuration of the relevant management software

Correct Answer: AD Section: (none)

QUESTION 4

A customer with an MSL8096 wants to extend the product's standard warrantyto 4 hours response time, 8.00 am to 9.00 pm local time, Monday through Friday, excluding HP holidays. Which HP service meets these requirements?

- A. HP Critical Service
- B. HP Support Plus
- C. HP Proactive 24
- D. HP Support Plus 24

Correct Answer: B Section: (none)

QUESTION 5

What must be installed and configured on SQL server connected to a P4000 SAN to perform a Zero Downtime Backup with HP Data Protector software?

- A. Central Management Console
- B. Snap Manager P4000
- C. VSS Hardware Provider

1

D. Application Snapshot Host Agent

Correct Answer: D Section: (none)

QUESTION 6

How can you improve throughput when designing a backup strategy using D2D backup systems?

- A. Ensure taht the block size of all data transfer is 64KB
- B. Create a separate SAN zone for each Fibre Channel port
- C. Arrange backup source data into multiple streams
- D. Use a single datastream for each backup job

Correct Answer: C Section: (none)

QUESTION 7

Which stgep should you take when designing an EBS environment for optimal performance?

- A. Make the primary storage the bottleneck
- B. Make the host the bottleneck
- C. Make the tape drive the bottleneck
- D. Make the switch the bottleneck

Correct Answer: C Section: (none)

QUESTION 8

When does the D2D deduplication housekeeping process run?

- A. at a default time of 12:00 p.m.
- B. at a user-defined scheduled time
- C. on-the-fly as the data is sent to the virtual library
- D. whenever a data cartridge is unloadedd and returned to its slot in the virtual library

Correct Answer: D Section: (none)

QUESTION 9

You have poor performance, even through original backup performance was not an issue. What is the likely source of this performance problem?

- A. the tape drive
- B. the disk subsystem
- C. the filesystem
- D. the network

Correct Answer: B Section: (none)

QUESTION 10

You have a tape driver with performance problem. You use HP Library and Tape Tools to determine the cause. Which test determines if the media is readable and provides block size and compression ratio?

- A. Media Analysis Test
- B. Media Validation Test
- C. Connectivity Test
- D. Device Analysis Test

Correct Answer: A Section: (none)

QUESTION 11

Which tool should you use to update the firmware of an ESL E-Series tape library?

- A. Remote Management Interface
- B. CommandView MSL
- C. CommandView TL
- D. Library and Tape Tools

Correct Answer: C Section: (none)

QUESTION 12

Waht must you do with Emulex HBAs connected to fabric switches when implementing an EBS solution? (selct two?

- A. Instal them in the last PCI slots of each server.
- B. Ensure that all entries in the registry for the HBAs are set to 0.
- C. Verify that he topology adapter parameter is set to 1
- D. Disable any unused ports.
- E. Verify that the link speed is the same for the HBA and the connected SAN switch port

Correct Answer: CE Section: (none)

QUESTION 13

What must you do in HP Data Protector software to raise the maximum number of multiplexed streams?

- A. Raise the Multiplexing value in the backup specification.
- B. Configure Load Balancing of backup steams in the specific backup job.
- C. Increase the COncurrency value in the device properties context.
- D. Enable Multiple Streams in the global configuration file.

Correct Answer: A Section: (none)

QUESTION 14

Which component in Symantec NetBackup solution is responsible for scheduling and tracking client backup?

- A. Media Server
- B. Cell Server
- C. Master Server
- D. Storage Manager

Correct Answer: C Section: (none)

QUESTION 15

Which HP software application provides web-based management of EBS devices compliant with HTTP, SNMP MIB-2 or DMI v2?

- A. HP Operations Manager
- B. HP Systems Insight Manager
- C. HP Library and Tape Tools