ISLEVER

JN0-130

juniper networks certified internet specialist.e(jncis-e)

DEMO

https://www.islever.com/jn0-130.html

https://www.islever.com/juniper.html

For the most up-to-date exam questions and materials, we recommend visiting our website, where you can access the latest content and resources.

QUESTION NO: 1

What are two purposes of the RSVP signaling protocol when configuring MPLS Label-Switched Paths (LSPs)? (Choose two.)

- A. to perform a labelpush operation
- B. to track the status of signaled LSPs
- C. to perform longest-match route lookups
- D. to reserve resources, such as labels and path information

Answer: B,D

QUESTION NO: 2

A Bridged 1483 network is grouping all DSL users into a single logical subnet. Which configuration command prevents the end users from directly communicating with each other?

- A. noip arp
- B. noip proxy-arp
- C. restrictip arp
- D. restrictip proxy-arp

Answer: B

QUESTION NO: 3

Which three BGP attributes are always communicated in a BGP update packet? (Choose three.)

- A. MED
- B. Origin
- C. AS Path
- D. Next Hop
- E. Aggregator

Answer: B,C,D

QUESTION NO: 4

What is the default Quality of Service traffic class used by the ERX Edge Router?

- A. bronze forwarding
- B. assured forwarding

1

C. expedited forwarding D. best effort forwarding
Answer: D
QUESTION NO: 5
When configuring an explicit path, what does the next-address entry identify?
A. the tunnel end pointB. the tunnel start pointC. a specific node to be traversedD. the node prior to the tunnel end point
Answer: A
QUESTION NO: 6
On a 3-port CT3 card, how many HDLC controllers does each port support?
A. 64 B. 128 C. 512 D. 1024
Answer: B
QUESTION NO: 7
Which type of hop in an ERO must be directly connected to the previous hop?
A. full B. strict C. loose D. partial
Answer: B
QUESTION NO: 8

Which configuration component is required to allow a PPP over ATM client to connect to one virtual router for a particular session and to a different virtual router for another session?

- A. profile
- B. domain map
- C. IP access-route
- D. static IP addressing

Answer: A

QUESTION NO: 9

Which IS-IS authentication method is supported on the ERX Edge Router?

- A. simple password
- B. HMAC message digest 5
- C. Password Authentication Protocol
- D. Challenge Handshake Authentication Protocol

Answer: B

QUESTION NO: 10

You would like to configure an Ethernet interface with the following characteristics: ?

Fast Ethernet port 3/2 ?

192.168.1.1/24 ? VLAN 21 ?

Description "SNMP-Mgmt"

Which set of configuration commands accurately completes this task?

A. interface fast 3/2

descriptionSNMP-Mgmt

encapylan

interfacefast 3/2.21

vlanid 21

ipaddress 192.168.1.1 255.255.255.0

B. interface fast 3/2

encapylan

interfacefast 3/2.21

vlanid 21

ipaddress 192.168.1.1 255.255.255.0

descriptionSNMP-Mgmt