

ISLEVER

JN0-201

juniper networks certified internet
associate.m(jncia-m)

DEMO

<https://www.islever.com/jn0-201.html>

<https://www.islever.com/juniper.html>

For the most up-to-date exam questions and materials, we recommend visiting our website, where you can access the latest content and resources.

QUESTION NO: 1

For which two functions is the Routing Engine responsible? (Choose two.)

- A. JUNOS software operation
- B. routing protocol control
- C. packet forwarding
- D. queuing functions

Answer: A,B

QUESTION NO: 2

The monitor traffic command closely resembles what UNIX based utility?

- A. ps -x
- B. ls -a-l
- C. passwd
- D. tcpdump

Answer: D

QUESTION NO: 3

Given the following configuration: interfaces { so-0/0/0 { unit 0 { family inet { address 10.10.10.1/24; } } } so-0/0/1 { unit 0 { family inet { address 20.20.20.1/24; } } } lo0 { unit 0 { family inet { address 192.168.1.1/32; } } } Which is considered an exception packet?

- A. IP packet addressed to 10.100.100.10
- B. ICMP traceroute packet with TTL set to 5
- C. IP packet with the Router Alert option set
- D. ICMP echo request addressed to 172.16.1.1

Answer: C

QUESTION NO: 4

During OSPF adjacency formation, in what state is a router when it is negotiating to be in charge of the database synchronization process?

- A. Exchange
- B. 2Way

-
- C. ExStart
 - D. Init

Answer: C

QUESTION NO: 5

Given the following configuration snippet: [edit protocols bgp] import remove-comm; group peer-65521 { type external; export [my-cust-tag add-as-path]; peer-as 65221; neighbor 192.168.20.1 { import [gold-cust silver-cust bronze-cust]; export add-metric; } neighbor 192.168.16.1 { export add-metric; } Which policy will be applied to neighbor 192.168.16.1 for inbound routes?

- A. add-metric
- B. gold-cust
- C. my-cust-tag
- D. remove-comm

Answer: D

QUESTION NO: 6

Which RSVP object assigns a label to the LSP?

- A. Label Object
- B. Label Request Object
- C. Record Route Object
- D. Label Assign Object

Answer: A

QUESTION NO: 7

During initial traffic flow, which routers do dense mode multicast protocols assume want to receive multicast traffic?

- A. only routers with receivers attached
- B. all routers in the network
- C. all routers along the shortest-path tree
- D. only routers along the core based tree

Answer: B

QUESTION NO: 8

Which two steps are required for RIP to redistribute IS-IS routes? (Choose two.)

- A. create a redistribution policy accepting the IS-IS routes
- B. create a redistribution policy accepting the RIP routes
- C. apply the redistribution policy to RIP as export
- D. apply the redistribution policy to RIP as import
- E. apply the redistribution policy to IS-IS as import
- F. apply the redistribution policy to IS-IS as export

Answer: A,C

QUESTION NO: 9

Which message is used to transport routing information between BGP peers?

- A. Open
- B. Active
- C. Keepalive
- D. Notification
- E. Update

Answer: E

QUESTION NO: 10

What are the three components of the ISO NET address? (Choose three.)

- A. N-selector
- B. ISO number
- C. MAC address
- D. System ID
- E. Area ID
- F. AS number

Answer: A,D,E

QUESTION NO: 11