

ISLEVER

JN0-202

M-series, Associate (JNCIA-M)

DEMO

<https://www.islever.com/jn0-202.html>

<https://www.islever.com/juniper.html>

For the most up-to-date exam questions and materials, we recommend visiting our website, where you can access the latest content and resources.

QUESTION NO: 1

Which command allows real-time monitoring of interface statistics on interface so-0/0/0?

- A. monitor interface so-0/0/0
- B. monitor traffic interface so-0/0/0
- C. monitorstatistics so-0/0/0
- D. monitor so-0/0/0

Answer: A

QUESTION NO: 2

Which command can be used to display information about packets that have been logged with the log firewall filter action?

- A. show log
- B. show log messages
- C. show firewall
- D. show firewall log

Answer: D

QUESTION NO: 3

To create a stable IBGP peering arrangement, it is recommended that internal peering be created between the loopback interfaces of the IBGP peering routers. Why is the local-address command required for successful connectivity in this scenario?

- A. to send the BGP Open message
- B. to tell the local router which interface the update is going to be received on
- C. to tell the local router which interface to source the update from
- D. to authenticate using MD5 between these neighbors

Answer: C

QUESTION NO: 4

How can you identify all routes that are more specific than 10.0/16, excluding the exact match?

- A. route-filter 10.0/16 longer
- B. route-filter 10.0.0/17 longer

-
- C. route-filter 10.0/16 or longer
 - D. route-filter 10.0.0/17 upto /32

Answer: A

QUESTION NO: 5

Which router feature will improve Routing Engine fail-over times?

- A. GRES
- B. RED
- C. MPLS
- D. VRRP

Answer: A

QUESTION NO: 6

Given the following policy:

```
policy-statement limit-cust {  
  from { route-filter 192.168.0.0/16 or longer accept; route-filter 192.168.8.0/21 longer;  
  route-filter 192.168.0.0/24 or longer {  
    metric 5;  
    reject;  
  }  
  then {  
    metric 10; accept;  
  }  
}
```

What happens to the route 192.168.9/24?

- A. The metric is set to 10, and the route is accepted.
- B. The metric is set to 5, and the route is rejected.
- C. The route is accepted.
- D. The route passes through this filter to the next.

Answer: A

QUESTION NO: 7

Which RSVP object allows for loop avoidance in the downstream direction?

- A. Record Route Object in Path Message
- B. Record Route Object in Reservation Message
- C. Tspec Object in Reservation Message
- D. Session Attribute Object in Path Message

Answer: A

QUESTION NO: 8

Given the following configuration:

```
interfaces {
  so-0/0/0 {
    unit 0 {
      family inet {
        address 10.10.10.1/24;
      }
    }
  }
  so-0/0/1 {
    unit 0 {
      family inet {
        address 20.20.20.1/24;
      }
    }
  }
  lo0 {
    unit 0 {
      family inet {
        address 192.168.1.1/32;
      }
    }
  }
}
```

What is considered an exception packet?

- A. ICMP traceroute packet with TTL set to 5
- B. ICMP echo request addressed to 192.168.1.1
- C. IP packet addressed to 192.168.100.100
- D. IP packet addressed to 10.100.100.10

Answer: B

QUESTION NO: 9

Which two statements are true about a T-Series Packet Forwarding Engine? (Choose two.)