

ISLEVER

JN0-320

Juniper Networks Certified Juniper DX (DXAP)
Associate Exam

DEMO

<https://www.islever.com/jn0-320.html>

<https://www.islever.com/juniper.html>

For the most up-to-date exam questions and materials, we recommend visiting our website, where you can access the latest content and resources.

QUESTION NO: 1

An enterprise uses a Web-tiered application that provides NTLM end-user authentication. What is the required Cluster option?

- A. Connection Binding
- B. Sticky Load Balancing
- C. DSR
- D. Connect Method

Answer: A

QUESTION NO: 2

Which Juniper DX service uses 3G Cache?

- A. Cluster
- B. Redirector
- C. Forwarder
- D. Server Load Balancer

Answer: A

QUESTION NO: 3

Which file should be sent to JTAC for all DX appliance support cases?

- A. tsdump file
- B. demo_override file
- C. tcpdump file
- D. nitro.apprule file

Answer: A

QUESTION NO: 4

An enterprise has multiple servers hosting the same application. The Juniper DX VIP is listening on IP address 64.10.10.1, port 80. Which three target server labels are correct? (Choose three.)

- A. 64.10.10.51:80
- B. 10.10.1.50:80
- C. 64.10.10.52:81

D. 64.10.10.1:80

E. 64.10.10.60

Answer: A,B,C

QUESTION NO: 5

Your administrator wants to centralize logs from the DX appliance and Cluster. Which two protocols are available to export those logs? (Choose two.)

A. SMTP

B. SCP

C. TFTP

D. syslog

Answer: B,D

QUESTION NO: 6

When configuring SMTP Health Check parameters for SLB, which two statements are true? (Choose two.)

A. SMTP health checking works with any SMTP application.

B. This parameter requires no configuration, it is enabled by default.

C. The DX appliance establishes a TCP connection for handshaking with the server.

D. SMTP health checking does not work with SMTPS, it only works with plain-text SMTP servers.

Answer: C,D

QUESTION NO: 7

In Unified Failover, if a Juniper DX appliance loses power, how does a standby unit assume the new master role?

A. The standby unit injects the VIP into the network using BGP4

B. The standby unit assigns its ether0 address to its VIP and advertises its new role to the network.

C. The standby unit injects the VIP into the network using RIP or OSPF.

D. The standby unit assumes the master's VIPs.

Answer: D

QUESTION NO: 8

Which Juniper DX service is used for load balancing UDP protocols such as NTP?

- A. SLB
- B. Redirector
- C. Cluster
- D. Forwarder

Answer: A

QUESTION NO: 9 DRAG DROP

Click the Task button.

A client makes a request for `www.yourcompany.com` which is using the Juniper DX GSLB feature, distributing traffic to the nearest site.

Place the flow steps in the correct order to demonstrate the GSLB process flow.

A client makes a request for `www.yourcompany.com` which is using the Juniper DX GSLB feature, distributing traffic to the nearest site. Place the flow steps in the correct order to demonstrate the GSLB process flow.

place here

place here

place here

place here

place here

yourcompany.com GSLB DNS

Client

www.yourcompany.com VIP

root (.com) DNS

Client's Local DNS

Flow 1

Flow 2

Flow 3

Flow 4

Flow 5

Done

Actual Tests

Answer: