ISLEVER

JN0-350

ER.Specialist(JNCIS-ER)

DEMO

https://www.islever.com/jn0-350.html https://www.islever.com/juniper.html

For the most up-to-date exam questions and materials, we recommend visiting our website, where you can access the latest content and resources.

Note: The answer is for reference only, you need to understand all question.

QUESTION 1

Which statement is true about external BGP peering sessions?

- A. A peer-group must be defined as type external.
- B. A peer-as must be configured for each peering session.
- C. You must specify a local-address for each peering session.
- D. You must specify a ttl for each peering session.

Answer: B

QUESTION 2

You want to determine what IP address and port number the router is using to NAT a particular connection. Which command will display this information?

- A. show services stateful-firewall flows
- B. show services session-table
- C. show services nat flows
- D. show services nat conversations

Answer: A

QUESTION 3

Which statement is true about the area-range command?

- A. When the area-range command is used, the ABR generates a default route.
- B. You can have only one area-range statement per OSPF area.
- C. The area-range command can only be used to summarize internal routes.
- D. The area-range statement can be configured under an NSSA area to summarize external routes.

Answer: D

QUESTION 4

You need to transport non-IP traffic between a branch office and headquarters. What is a valid connectivity option?

A. MPLS Layer 3 VPN

1

- B. IPSec tunnel
- C. MPLS Layer 2 VPN
- D. IP in IP tunnel

Answer: C

QUESTION 5

Exhibit:

```
[edit firewall filter example]
User@Router#show
term count-traffic {
    from {
        source-address {
            10.10.0.0/16;
        }
    }
    then count valid-source;
}
term discard-traffic {
    then [
        discard;
    }
}
```

You work as a network administrator at . You study the exhibit carefully. In the exhibit, what will be the result of a packet sourced from address 10.10.1.1 when the filter is applied?

- A. The packet will be counted and then discarded.
- B. The packet will be counted and then accepted.
- C. The packet will be accepted with no other action.
- D. The packet will be discarded with no other action.

Answer: B

QUESTION 6

Which two features can you configure to optimize the processing of VoIP traffic? (Choose two.)

- A. H.323 proxy
- B. Compressed Real-Time Transport Protocol
- C. Multiclass Multilink PPP
- D. SIP compression

Answer: BC

QUESTION 7

2

Which two statements are true with regard to outbound BGP policies in a dual homed scenario? (Choose two.)

- A. To enforce strict primary/secondary outbound routing only default routes should be received from both your ISPs.
- B. To enforce load-sharing between both ISPs, when multiple routers are used, configurations should not be synchronized between them.
- C. To enforce strict primary/secondary outbound routing full BGP routes should be received from both your ISPs.
- D. To enforce load-sharing between both ISPs, when multiple routers are used, configurations should be synchronized between them.

Answer: AD

QUESTION 8

You are configuring a router under [edit services nat]. Which command will configure the router to perform Network Address Port Translation (NAPT/PAT)?

- A. set pool my-pool port automatic
- B. set pool my-pool port overload
- C. set rule my-rule term 1 then translated overload
- D. set rule my-rule term 1 then translated port automatic

Answer: A

QUESTION 9

Which two statements are true about scheduler maps? (Choose two.)

- A. A scheduler map controls the resources assigned to a specific queue.
- B. A scheduler map is applied before a multifield firewall filter.
- C. A default scheduler map is applied to each interface.
- D. A scheduler map is only needed on low speed interfaces.

Answer: AC

QUESTION 10

Exhibit: