

ISLEVER

JN0-521

FWV.Associate (JNCIA-FWV)

DEMO

<https://www.islever.com/jn0-521.html>

<https://www.islever.com/juniper.html>

For the most up-to-date exam questions and materials, we recommend visiting our website, where you can access the latest content and resources.

QUESTION NO: 1

A ScreenOS firewall has the correct interfaces addressed and active. A policy is written allowing interzone FTP traffic from a directly connected client. But the traffic does not cross the firewall from the client to the server. What is the most likely problem with the firewall?

- A. The ScreenOS firewall has no physical connection to the FTP server.
- B. The ALG option on the ScreenOS firewall has not been enabled for FTP traffic.
- C. The ScreenOS firewall does not have a route defined to the FTP servers' subnet.
- D. The ScreenOS firewall does not have a route defined to the FTP clients subnet.

Answer: C

QUESTION NO: 2

Click the Exhibit button. In the exhibit, why is the packet dropped?

```
***** 20988.0: <public/ethernet0/1> packet received [60]*****
ipid = 19135(4abf), @d78c4870
packet passed sanity check.
ethernet0/1:10.1.75.250/17664->10.1.10.5/512,1(8/0)<Root>
chose interface ethernet0/1 as incoming nat if.
IP classification from non-shared src if : vsys Root
search route to (10.1.75.250->10.1.10.5) in vr untrust-vr for 0/0
route 10.1.10.5->10.1.1.254, to ethernet0/0
routed (10.1.10.5, 0.0.0.0) from ethernet0/1 (ethernet0/1 in 0) to
ethernet0/0
IP classification from non-shared dst if : vsys Root
policy search from zone 1002-> zone 1000
vsys Root: ethernet0/1->ethernet0/0, policy zone 1002->1000(1000),
10.1.75.250-> 10.1.10.5
Searching global policy.
packet dropped, denied by policy ActualTests
```

- A. interface down
- B. route not configured
- C. policy not configured
- D. denied by policy 1005

Answer: C

QUESTION NO: 3

Which three options allow proper configuration of NAT-dst? (Choose three.)

- A. the default address book entry of "any" in the internal zone
- B. the default address book entry of "any" in the external zone

-
- C. a secondary address on one of the interfaces in the internal zone
 - D. an address book entry for the address to be translated in the internal zone
 - E. a static route to the appropriate subnet using a private interface as the outbound interface

Answer: C,D,E

QUESTION NO: 4

Which two statements are true in regards to a ScreenOS firewall in transparent mode? (Choose two.)

- A. VPNs can terminate to the VLAN1 interface IP address
- B. Static routes must be configured if multiple virtual routers are going to be used.
- C. It can be installed in a network without the requirement to reconfigure IP addressing schemes.
- D. You must use the console port to manage the device as you cannot manage the device using an Ethernet port.

Answer: A,C

QUESTION NO: 5

What are three major concerns when sending private data over a public medium? (Choose three.)

- A. integrity
- B. authority
- C. capacity
- D. confidentiality
- E. authentication

Answer: A,D,E

QUESTION NO: 6

By default, from which hardware component is the startup copy of the ScreenOS loaded?

- A. NVRAM
- B. TFTP server
- C. internal flash
- D. PCMCIA card

Answer: C

QUESTION NO: 7

Which three must a policy contain? (Choose three.)

- A. action
- B. service
- C. address
- D. application
- E. policy name

Answer: A,B,C

QUESTION NO: 8

What is the default mode for an interface in the trust zone?

- A. NAT
- B. route
- C. Layer 2
- D. Layer 3
- E. transparent

Answer: A

QUESTION NO: 9

Which command is used to verify IKE Phase 1 is complete?

- A. get sa active
- B. get ike active
- C. get ike cookie
- D. get flow active

Answer: C

QUESTION NO: 10

When managing a ScreenOS device using the WebUI and performing an image upgrade, from which hardware component will the ScreenOS image be loaded?