

ISLEVER

# JN0-694

Enterprise Routing and Switching Support,  
Professional (JNCSP-ENT)

DEMO

<https://www.islever.com/jn0-694.html>

<https://www.islever.com/juniper.html>

For the most up-to-date exam questions and materials, we recommend visiting our website, where you can access the latest content and resources.

---

**QUESTION NO: 1**

You are implementing Q-in-Q tunneling on an EX Series switch. You want the tunnel to support all C-VLANs; however, only some VLANs are able to send traffic across the tunnel. Switch-1 has the following configuration:

[edit vlans]

```
user@Switch-1# show
```

```
v100 {  
  vlan-id 100;  
  interface {  
    ge-0/0/0.10;  
    ge-0/0/1.20;  
  }  
  dot1q-tunneling {  
    customer-vlans [ ];  
  }  
}
```

What would solve this problem?

- A. Add family ethernet-switching to the tunnel-side interface on Switch-1.
- B. Implement RSTP.
- C. Q-in-Q tunneling will not work in this scenario; use a Layer 2 VPN instead.
- D. Remove the customer-vlans statement.

**Answer: C**

**Explanation:**

**QUESTION NO: 2**

You are troubleshooting a problem where an OSPF adjacency between two neighboring routers will not form.

---

What are two reasons for this problem? (Choose two.)

- A. One or both of the connected interfaces are missing the family inet statement.
- B. One or both of the connected interfaces are missing the family iso statement.
- C. The connected interfaces are not on the same subnet.
- D. Another IGP is running on one or both of the routers, overriding OSPF.

**Answer: B,D**

**Explanation:**

### QUESTION NO: 3

Your Junos device is dropping certain traffic flows, while allowing other traffic flows to pass through the device unaffected.

Which CoS component is causing this problem?

- A. BA classification
- B. RED
- C. MF classification
- D. Rewrite rules

**Answer: D**

**Explanation:**

### QUESTION NO: 4

Two neighboring routers are able to form an OSPF adjacency, but are not able to establish an IBGP neighborhood.

What are two reasons for the IBGP neighborhood problem? (Choose two.)

- A. One of the devices has a misconfigured BGP peer address.
- B. One or both of the connected interfaces are missing the family iso statement.
- C. OSPF has a lower route preference than BGP.
- D. A firewall filter on one of the interfaces is blocking TCP traffic.

**Answer: B,C**

**Explanation:**

---

**QUESTION NO: 5**

Your switch is experiencing a problem where a port that should have only one host connected occasionally shows that multiple MAC addresses are being learned.

Which configuration setting would ensure that no extra hosts can join the network using this switch port?

- A. mac-limit
- B. no-mac-learning
- C. persistent-learning
- D. bpdu-block-on-edge

**Answer: D**

**Explanation:**

**QUESTION NO: 6**

You are having problems redistributing RIP routes into OSPF. Your Junos device has the following configuration:

```
[edit protocols ospf]
user@router# show
import my-policy;
area 0.0.0.0 {
  interface ge-0/0/0.0;
  interface ge-0/0/ ;
  interface ge-0/0/ {
    passive;
  }
}
```