

ISLEVER

# JN0-730

DX, Specialist (JNCIS-DX)

DEMO

<https://www.islever.com/jn0-730.html>

<https://www.islever.com/juniper.html>

For the most up-to-date exam questions and materials, we recommend visiting our website, where you can access the latest content and resources.

---

**QUESTION NO: 1**

What is the initial default username and password for all ScreenOS devices?

- A. administrator/password
- B. root/password
- C. netscreen/netscreen
- D. admin/netscreen1

**Answer: D**

**Explanation:**

**QUESTION NO: 2**

Which operating system is used on a NetScreen device?

- A. IOS
- B. Junos
- C. FreeBSD
- D. ScreenOS

**Answer: A**

**Explanation:**

**QUESTION NO: 3**

When is NAT used?

- A. for Layer 2 switching
- B. for MPLS VPNs
- C. to translate between IP addresses
- D. for secure tunnels

**Answer: B**

**Explanation:**

**QUESTION NO: 4**

---

What is a zone used for?

- A. to bundle interfaces together for redundancy
- B. to bundle interfaces sharing identical security requirements
- C. to provide a tunneled connection across a network
- D. to protect against spam attacks

**Answer: D**

**Explanation:**

**QUESTION NO: 5**

Which two devices run ScreenOS software? (Choose two.)

- A. NetScreen-5200
- B. NetScreen-5400
- C. SRX240
- D. MX480

**Answer: C,D**

**Explanation:**

**QUESTION NO: 6**

Which security feature provides secure tunnels across a public network?

- A. dynamic routing
- B. Web filtering
- C. IPsec
- D. firewall filters

**Answer: A**

**Explanation:**

**QUESTION NO: 7**

By default, from which hardware component is the startup copy of the ScreenOS loaded?

- 
- A. ROM
  - B. NVRAM
  - C. TFTP server
  - D. Internal Flash
  - E. PCMCIA Card

**Answer: D**

**Explanation:**

#### **QUESTION NO: 8**

Using the CLI, if the startup copy of the ScreenOS on a NS-204 is corrupted, from which two (2) alternate locations can an image be loaded?

- A. ROM
- B. TFTP server
- C. Internal Flash
- D. PCMCIA Card
- E. Compact Flash Card

**Answer: B,E**

**Explanation:**

#### **QUESTION NO: 9**

By default, from which hardware component is the startup copy of the ScreenOS loaded?

- A. NVRAM
- B. TFTP server
- C. internal flash
- D. PCMCIA card

**Answer: C**

**Explanation:**

#### **QUESTION NO: 10**

Using the CLI, if the startup copy of the ScreenOS is corrupted, from which location can an image be loaded?