ISLEVER

MA0-101

McAfee Certified Product Specialist - NSP

DEMO

https://www.islever.com/ma0-101.html https://www.islever.com/mcafee.html

For the most up-to-date exam questions and materials, we recommend visiting our website, where you can access the latest content and resources.

QUESTION NO: 1

Which port needs to be opened for Alert Channel communication between Sensor and Manager through a firewall?

A. 8501

- **B.** 8502
- **C.** 8503
- **D.** 8555

Answer: B Explanation:

QUESTION NO: 2

Setting a threshold to allow an IPS to react when traffic volume exceeds the set limit is an example of what type of detection method?

- A. Signature based
- B. Pattern matching
- C. Denial of Service
- D. Remediation

Answer: C Explanation:

QUESTION NO: 3

Performance debugging mode can be enabled on a sensor for a specified time duration by issuing which of the following CLI commands?

- A. sensor perf-debug 100
- B. sensor perf-debug on 100
- **C.** sensor perf-debug Interface all 100
- D. sensor perf-debug assert 100

Answer: A Explanation:

QUESTION NO: 4

What type of encryption is used for file transfers between the Sensor and the Manager?

A. SSL with RC4
B. SSL with MD5
C. SSL with RC4 and MD5
D. DES

Answer: D Explanation:

QUESTION NO: 5

When placed in Layer3 mode, a Sensor detects a Layer2 device based on which of the following?

A. MAC addressB. IP addressC. DNSD. Subnet

Answer: B Explanation:

QUESTION NO: 6

What is the CLI command that enables the output of the MAC/IP address mapping table to the sensor debug files?

A. arp spoof statusB. arp spoof enableC. arp dumpD. arp flush

Answer: C Explanation:

QUESTION NO: 7

DoS detection is implemented in which of the following modes? (Choose two)

- A. Learning mode
- B. Configuration mode
- C. Threshold mode
- D. Bidirectional mode
- E. Inbound mode

Answer: A,C Explanation:

QUESTION NO: 8

Which port needs to be opened for Packet Log Channel communication between Sensor and Manager through a firewall?

A. 8501

B. 8502

C. 8503

D. 8555

Answer: C Explanation:

QUESTION NO: 9

Which port is correctly defined for the Alert Channel on the Network Security Manager?

- **A.** 8500**B.** 8501**C.** 8502
- **D.** 8504

Answer: C Explanation:

QUESTION NO: 10