

ISLEVER

N10-006

CompTIA Network+

DEMO

<https://www.islever.com/n10-006.html>

<https://www.islever.com/comptia.html>

For the most up-to-date exam questions and materials, we recommend visiting our website, where you can access the latest content and resources.

Topic 1, Network Architecture

QUESTION NO: 1

A technician has verified that a recent loss of network connectivity to multiple workstations is due to a bad CAT5 cable in the server room wall. Which of the following tools can be used to locate its physical location within the wall?

- A. Cable certifier
- B. Multimeter
- C. Cable tester
- D. Toner probe

Answer: D

Explanation:

QUESTION NO: 2

Which of the following is used to authenticate remote workers who connect from offsite? (Select TWO).

- A. OSPF
- B. VTP trunking
- C. Virtual PBX
- D. RADIUS
- E. 802.1x

Answer: D,E

Explanation:

QUESTION NO: 3

Which of the following network infrastructure implementations would be used to support files being transferred between Bluetooth-enabled smartphones?

- A. PAN
- B. LAN
- C. WLAN
- D. MAN

Answer: A

Explanation:

QUESTION NO: 4

Which of the following would be used in an IP-based video conferencing deployment? (Select TWO).

- A. RS-232
- B. 56k modem
- C. Bluetooth
- D. Codec
- E. SIP

Answer: D,E

Explanation:

QUESTION NO: 5

Which of the following helps prevent routing loops?

- A. Routing table
- B. Default gateway
- C. Route summarization
- D. Split horizon

Answer: D

Explanation:

QUESTION NO: 6

Which of the following is MOST likely to use an RJ-11 connector to connect a computer to an ISP using a POTS line?

- A. Multilayer switch
- B. Access point
- C. Analog modem
- D. DOCSIS modem

Answer: C

Explanation:

QUESTION NO: 7

An administrator has a virtualization environment that includes a vSAN and iSCSI switching. Which of the following actions could the administrator take to improve the performance of data transfers over iSCSI switches?

- A. The administrator should configure the switch ports to auto-negotiate the proper Ethernet settings.
- B. The administrator should configure each vSAN participant to have its own VLAN.
- C. The administrator should connect the iSCSI switches to each other over inter-switch links (ISL).
- D. The administrator should set the MTU to 9000 on the each of the participants in the vSAN.

Answer: D

Explanation:

QUESTION NO: 8

A network topology that utilizes a central device with point-to-point connections to all other devices is which of the following?

- A. Star
- B. Ring
- C. Mesh
- D. Bus

Answer: A

Explanation:

QUESTION NO: 9

A technician is connecting a NAS device to an Ethernet network. Which of the following technologies will be used to encapsulate the frames?

- A. HTTPS
- B. Fibre channel