

ISLEVER

NS0-505

NetApp Certified Implementation Engineer -
SAN Specialist, E-Series

DEMO

<https://www.islever.com/ns0-505.html>

<https://www.islever.com/netapp.html>

For the most up-to-date exam questions and materials, we recommend visiting our website, where you can access the latest content and resources.

QUESTION 1

Which item can be downloaded concurrently with controller firmware? (Choose the best answer.)

- A. SANtricity software
- B. NVSRAM
- C. ESM firmware
- D. Drive firmware

Answer: B

QUESTION 2

What should you do to confirm a component failure prior to replacing hardware? (Choose the best answer.)

- A. Run the Recovery Guru
- B. Run chkdsk on the client
- C. Check the Major Events Log
- D. Power cycle the storage array

Answer: A

QUESTION 3

When you arrive on a customer site, you discover that the customer network administrator has called in sick. While required power has been provided and all of the components ordered have been physically accounted for, the network will not be operational today. Which would be the most useful tool to complete your rack & stack and initial configuration of the system? (Choose the best answer.)

- A. a Serial Port cable
- B. a CD containing the 10.86 version of SANtricity
- C. a standalone switch or hub
- D. None of the above, come back tomorrow.

Answer: B

QUESTION 4

Consult the _____ to determine the current link status of a host port. (Choose the best answer.)

- A. Storage Array Profile
- B. Real-time performance monitor
- C. Recovery Guru
- D. Unreadable Sectors log

Answer: A

QUESTION 5

What is SMAgent? (Choose the best answer.)

- A. a host server process that enables storage system management with the storage data path
- B. an OS-dependent collection of utilities for servers attached to SANtricity-managed storage systems
- C. a GUI or CLI run on a host server used for storage system management
- D. a host I/O performance modeling interface
- E. inter-process communication that supports computer program subroutines

Answer: A

QUESTION 6

What system file is used during the controller start-of-day sequence to determine various SCSI parameters and other host-type specific settings for an E-Series system? (Choose the best answer.)

- A. Major Event Log
- B. ESM Firmware

C. NVSRAM

D. Unreadable Sectors Log

Answer: C

QUESTION 7

The ability of many E-Series controllers to hold an additional firmware image in reserve _____.

(Choose the best answer.)

A. is used to store a backup boot image

B. allows controller firmware to be downloaded immediately and activated at a later time

C. allows two firmware images to be used at the same time D. is used for Support use only

Answer: C

QUESTION 8

Review the diagram.

Is this cabling correct or incorrect, and why? (Choose the best answer.)

A. The cabling is incorrect because each controller goes to only one stack of disk shelves

B. The cabling is correct for the dual stack cabling method

C. The cabling is incorrect because it uses the top-down bottom-up cabling method

D. The cabling is incorrect because the controllers are cabled from the host port.

Answer: B

QUESTION 9

Which component of an E-Series storage system should always be upgraded first? (Choose the best answer.)