

ISLEVER

NS0-910

Network Appliance NetCache Internet Access
and Security Exam

DEMO

<https://www.islever.com/ns0-910.html>

<https://www.islever.com/netapp.html>

For the most up-to-date exam questions and materials, we recommend visiting our website, where you can access the latest content and resources.

QUESTION NO: 1

Which FOUR will best prevent client disruption caused by hardware failure when using multiple proxies? (Choose 4)

- A. transparency utilizing WCCP
- B. direct browser configuration
- C. autoconfiguration using a proxy.pac file
- D. round-robin DNS
- E. load balancer

Answer: A,C,D,E

QUESTION NO: 2

Which vector point is used to route an object to the ICAP server from NetCache, but before the data is requested from the Web server?

- A. RESPMOD_PRECACHE
- B. RESPMOD_POSTCACHE
- C. REQMOD_POSTCACHE
- D. REQMOD_PRECACHE

Answer: C

QUESTION NO: 3

Which FOUR are key steps in the authentication process? (Choose 4)

- A. verify protocol authentication settings (authenticates the user)
- B. verify ACL permission settings for the applicable group in the NetCache user database
- C. verify whether SmartFilter or WebWasher DynaBLocator denies the request
- D. allow or deny the request, based on the results of the authentication process
- E. verify connectivity to logging server

Answer: A,B,C,D

QUESTION NO: 4

Of the following choices, which TWO are paths to configure logging? (Choose 2)

- A. Setup > Maintenance > Logging

-
- B. Setup > System > Logging
 - C. Setup > Utilities > Logging
 - D. Setup > HTTP > Logging

Answer: B,D

QUESTION NO: 5

Which TWO implementations are required for setting up transparency with WCCP? (Choose 2)

- A. The WCCP router must be located where a firewall that uses Network Address Translation (NAT) is located between the WCCP and the NetCache appliance.
- B. The WCCP router has to be directly connected to the proxy.
- C. The WCCP router must be located where a firewall that uses Network Address Translation (NAT) is not located between the WCCP and the NetCache appliance.
- D. The WCCP router must be located so that it can view all network traffic for the clients that it is expected to serve.

Answer: C,D

QUESTION NO: 6

The NetCache appliance supports up to _____ SNMP communities.

- A. 32
- B. 8
- C. 4
- D. 16

Answer: B

QUESTION NO: 7

The NetCache appliance supports up to _____ SNMP communities.

- A. 32
- B. 16
- C. 4
- D. 8

Answer: D

QUESTION NO: 8

Which protocol entries are recorded in the Web access log file?

- A. Telnet, SNMP, SSH
- B. HTTP, FTP, RTSP
- C. HTTP, FTP, Gopher
- D. RTSP, NNTP

Answer: C

QUESTION NO: 9

Which FOUR cache control headers below are valid? (Choose 4)

- A. Cache-Control: private
- B. Cache-Control: no-store
- C. Pragma: no-cache
- D. Pragma: do-not-cache
- E. Cache-Control: no-cache

Answer: A,B,C,E

QUESTION NO: 10

Given the following service farm configuration, which request will be directed to the ICAP application?

```
config.icapv1.farm3.attr = \marketing_req_precache REQMOD_PRECACHE on rr on weak
```

- A. Requests about to be initiated by NetCache to the server
- B. Requests from the client before NetCache has initiated a request to the server
- C. Responses to requests initiated by NetCache before being cached on disk
- D. Requests from the client after NetCache has initiated a request to the server
- E. Responses to requests initiated by NetCache after being cached on disk

Answer: B

QUESTION NO: 11